EATON FULLER MEDIUM-DUTY TRANSMISSIONS FS-5306A



RANSMISSION Eaton-Fuller 530	06 6/1	
Capacity: 8,51 liter		
JSE		climate Moderate
Highway use, initial service		
PRODUCT RECOMMENDATION 1 Multifleet SCD 50	PRODUCT RECOMMENDATION 2 Multifleet SCD 40	Gear Oil Alcat 50
	Multimeet 305 40	Gear On Alcat 30
Change every 8000 km		0.44475
use Highway use, initial service		climate Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	Alono
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 8000 km	Cour on Anout co	
JSE		CLIMATE
Off-Highway use, severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gear Oil Alcat 50
 Check every 40 hours, change eve	ery 500 hours	
JSE		CLIMATE
Off-Highway use, severe		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Check every 40 hours, change eve	ry 500 hours	
JSE		CLIMATE
Off-Highway use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gear Oil Alcat 50
Check every 40 hours, change eve	ry 1000 hours	
JSE		CLIMATE
Off-Highway use		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
	Gear Oil Alcat 30	
Multifleet SCD 30		
	ry 1000 hours	
Check every 40 hours, change eve	ry 1000 hours	CLIMATE
Multifleet SCD 30 Check every 40 hours, change eve use Highway use	ry 1000 hours	climate Moderate
Check every 40 hours, change eve	PRODUCT RECOMMENDATION 2	

PRODUCT RECOMMENDATION

EATON FULLER MEDIUM-DUTY TRANSMISSIONS FS-5306A



use Highway use		climate Arctic		
			PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SCD 30	Gear Oil Alcat 30			
Charle over 15000 km charge over 20000 km				

Check every 16000 km, change every 80000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.