

EATON FULLER HEAVY-DUTY TRANSMISSIONS 5 -> 7 SPEED T-955AL



TRANSMISSION Eaton-Fuller 955AL 6/2
Capacity: 11,83 liter

USE Off-Highway use, severe		CLIMATE Moderate
---------------------------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 HDX 50	PRODUCT RECOMMENDATION 2 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 3 Unigear HS GL-3/GL-5 80W-90
--	--	---

Check every 40 hours, change every 500 hours

USE Off-Highway use, severe		CLIMATE Arctic
---------------------------------------	--	--------------------------

PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
---	--	--

Check every 40 hours, change every 500 hours

USE Off-Highway use		CLIMATE Moderate
-------------------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 HDX 50	PRODUCT RECOMMENDATION 2 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 3 Unigear HS GL-3/GL-5 80W-90
--	--	---

Check every 40 hours, change every 1000 hours

USE Off-Highway use		CLIMATE Arctic
-------------------------------	--	--------------------------

PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
---	--	--

Check every 40 hours, change every 1000 hours

USE Highway use		CLIMATE Moderate
---------------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 HDX 50	PRODUCT RECOMMENDATION 2 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 3 Unigear HS GL-3/GL-5 80W-90
--	--	---

Check every 1600 km, change every 40000 km

USE Highway use		CLIMATE Arctic
---------------------------	--	--------------------------

PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
---	--	--

Check every 1600 km, change every 40000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.