EATON FULLER HEAVY-DUTY TRANSMISSIONS 5 -> 7 SPEED T-11607B



TRANSMISSION Eaton-Fuller 11607 7/1 Capacity: 13 liter			
USE		CLIMATE	
Off Highway use, initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Multifleet SCD 50	Multifleet SCD 40	HDX 50	
Change every 30 hours			
USE		CLIMATE	
Off Highway use, initial service		Arctic	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Multifleet SCD 30	Multifleet SCD 20W-20	HDX 30	
Change every 30 hours			
USE		CLIMATE	
Highway use, initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Multifleet SCD 50	Multifleet SCD 40	HDX 50	
Change every 8000 km			
USE		CLIMATE	
Highway use, initial service		Arctic	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Multifleet SCD 30	Multifleet SCD 20W-20	HDX 30	
Change every 8000 km			
USE		CLIMATE	
Off-Highway use, severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Multifleet SCD 50	Multifleet SCD 40	HDX 50	
Check every 40 hours, change every 500 hours			
USE		CLIMATE	
Off-Highway use, severe		Arctic	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Multifleet SCD 30	Multifleet SCD 20W-20	HDX 30	
Check every 40 hours, change every 500 hours			
USE		CLIMATE	
Off-Highway use		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Multifleet SCD 50	Multifleet SCD 40	HDX 50	
Check every 40 hours, change every 1000 hours			

Check every 40 hours, change every 1000 hours

EATON FULLER HEAVY-DUTY TRANSMISSIONS 5 -> 7 SPEED T-11607B



USE		CLIMATE	
Off-Highway use		Arctic	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Multifleet SCD 30	Multifleet SCD 20W-20	HDX 30	
Check every 40 hours, change every 1000 hours			
USE		CLIMATE	
Highway use		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Multifleet SCD 50	Multifleet SCD 40	HDX 50	
Check every 16000 km, change every 80000 km			
USE		CLIMATE	
Highway use		Arctic	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Multifleet SCD 30	Multifleet SCD 20W-20	HDX 30	
Check every 16000 km, change every 80000 km			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.