

EATON FULLER HEAVY-DUTY TRANSMISSIONS 9 SPEED RTLOC-16909A- T2



TRANSMISSION Eaton-Fuller 16909 9
Capacity: 13,2 liter

USE	CLIMATE
Off Highway use, initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gear Oil Alcat 50

Change every 30 hours

USE	CLIMATE
Off Highway use, initial service	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	Gear Oil Alcat 30	

Change every 30 hours

USE	CLIMATE
Highway use, initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gear Oil Alcat 50

Change every 8000 km

USE	CLIMATE
Highway use, initial service	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	Gear Oil Alcat 30	

Change every 8000 km

USE	CLIMATE
Off-Highway use, severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gear Oil Alcat 50

Check every 40 hours, change every 500 hours

USE	CLIMATE
Off-Highway use, severe	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	Gear Oil Alcat 30	

Check every 40 hours, change every 500 hours

USE	CLIMATE
Off-Highway use	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gear Oil Alcat 50

Check every 40 hours, change every 1000 hours

EATON FULLER HEAVY-DUTY TRANSMISSIONS 9 SPEED RTLOC-16909A- T2



USE		CLIMATE
Off-Highway use		Arctic
PRODUCT RECOMMENDATION 1 Multifleet SCD 30	PRODUCT RECOMMENDATION 2 Gear Oil Alcat 30	
<i>Check every 40 hours, change every 1000 hours</i>		
USE		CLIMATE
Highway use		Moderate
PRODUCT RECOMMENDATION 1 Multifleet SCD 50	PRODUCT RECOMMENDATION 2 Multifleet SCD 40	PRODUCT RECOMMENDATION 3 Gear Oil Alcat 50
<i>Check every 16000 km, change every 160000 km</i>		
USE		CLIMATE
Highway use		Arctic
PRODUCT RECOMMENDATION 1 Multifleet SCD 30	PRODUCT RECOMMENDATION 2 Gear Oil Alcat 30	
<i>Check every 16000 km, change every 160000 km</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.