EATON FULLER HEAVY-DUTY TRANSMISSIONS 9 SPEED RTO-13109B-ATE



TRANSMISSION Eaton-Fuller 13109 9/ Capacity: 42 liter	/1	
USE		CLIMATE
Off Highway use, initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 10W	Gear Oil Alcat 10W	ATF Dexron II-D
Change every 30 hours		
USE		CLIMATE
Highway use, initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 10W	Gear Oil Alcat 10W	ATF Dexron II-D
Change every 2500 km		
USE		CLIMATE
Off-Highway use, severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 10W	Gear Oil Alcat 10W	ATF Dexron II-D
Check every 40 hours, change every 50	0 hours	
USE		CLIMATE
Off-Highway use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 10W	Gear Oil Alcat 10W	ATF Dexron II-D
Check every 40 hours, change every 10	00 hours	
USE		CLIMATE
Highway use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 10W	Gear Oil Alcat 10W	ATF Dexron II-D
Check every 4000 km, change every 80	000 km/ 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.