

**ERF E6 E6.18 (1986-1993)**

**ENGINE** Cummins 6BTA180  
Capacity: 14 liter

| USE                           |                               | CLIMATE       |
|-------------------------------|-------------------------------|---------------|
| Normal                        |                               | Mediterranean |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      |               |
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |               |

*Change every 8000 km*

| USE                         |                               | CLIMATE  |
|-----------------------------|-------------------------------|----------|
| Normal                      |                               | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      |          |
| <b>Synfleet SHPD 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |          |

*Change every 8000 km*

**DIFFERENTIAL REAR (4x2) Rockwell**

| USE                         |                                    | CLIMATE                      |
|-----------------------------|------------------------------------|------------------------------|
| Normal                      |                                    | Moderate                     |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           | PRODUCT RECOMMENDATION 3     |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> | <b>Gearlube GL-5 85W-140</b> |

*Check every 16000 km, change every 200000 km/ 12 months*

**TRANSMISSION MANUAL** Eaton 4106 6/1  
Capacity: 7,5 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Gear 5015</b>      | <b>Gearlube GL-4 80W</b> |          |

*Check every 16000 km, change every 100000 km*

**TRANSMISSION MANUAL** Eaton 6109 9/1  
Capacity: 8 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Gear 5015</b>      | <b>Gearlube GL-4 80W</b> |          |

*Check every 16000 km, change every 100000 km*

**ERF E6 E6.18 (1986-1993)****HYDRAULIC CAB TILT SYSTEM**

Capacity: 0,43 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****ATF Dexron II-D***Check every 16000 km***HYDRAULIC CLUTCH SYSTEM**

Capacity: 0,6 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Drauliquid DOT 3****POWER STEERING****USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****ATF Dexron II-D***Change every 200000 km/ 12 months***GREASE POINTS/NIPPLES****USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2***Change every 16000 km***GREASE POINTS/NIPPLES TRAILER COUPLING**

We are unable to give a standard recommendation for this component. Please contact our service department.

**GREASE POINTS/NIPPLES WHEEL BEARINGS****USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2***Change every 16000 km*

**ERF E6 E6.18 (1986-1993)****COOLING SYSTEM**

Capacity: 24 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

*Change every 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*