

# FORD OTOSAN CARGO CARGO 2530 6X2 (2004-2007)



**ENGINE** Ford EcoTorq  
Capacity: 28 liter

| USE                           |                               | CLIMATE  |
|-------------------------------|-------------------------------|----------|
| Normal                        |                               | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      |          |
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |          |

**DIFFERENTIAL REAR** Meritor RS186  
Capacity: 20 liter

| USE                          |                                     | CLIMATE  |
|------------------------------|-------------------------------------|----------|
| Normal                       |                                     | Moderate |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |          |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |          |

**TRANSMISSION MANUAL** ZF 16S-109 16/2  
Capacity: 8,5 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-4 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

**HYDRAULIC CLUTCH SYSTEM**  
Capacity: 0,4 liter

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

**POWER STEERING**  
Capacity: 3,5 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>ATF Dexron II-D</b>   |  |          |

# FORD OTOSAN CARGO CARGO 2530 6X2 (2004-2007)



## GREASE POINTS/NIPPLES KING PINS

Capacity: 15 grams (each side)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| HT Q9 High Grade Grease  |  |          |

## GREASE POINTS/NIPPLES WHEEL BEARINGS DRIVE AXLE

Capacity: 200 grams (each side)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| HT Q9 High Grade Grease  |  |          |

## GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

Capacity: 100 grams (each side)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| HT Q9 High Grade Grease  |  |          |

## GREASE POINTS/NIPPLES WHEEL BEARINGS TAG AXLE

Capacity: 150 grams (each side)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| HT Q9 High Grade Grease  |  |          |

## COOLING SYSTEM

Capacity: 17,5 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+           | Coolant SP 12            | Coolant -38 Organic NF   |

## AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

# FORD OTOSAN CARGO CARGO 2530 6X2 (2004-2007)



*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*