

FORD (USA) F-550 (SUPER DUTY) F-550 5.4 V8 SUPER DUTY (2008-2010)



ENGINE Triton
Capacity: 6,6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

Check every 1 months, change every 7500 miles/ 6 months

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

Check every 1 months, change every 5000 miles/ 6 months/ 200 hours

DIFFERENTIAL REAR Dana S110/S130
Capacity: 6,6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 105000 miles

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 50000 miles

TRANSMISSION AUTOMATIC TorqShift 5R110 5/1
Capacity: 16,6 liter (Dry fill)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

PRODUCT RECOMMENDATION 2

SP Matic 2032

Check every 15000 miles, change every 60000 miles

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

PRODUCT RECOMMENDATION 2

SP Matic 2032

Change every 30000 miles

FORD (USA) F-550 (SUPER DUTY) F-550 5.4 V8 SUPER DUTY (2008-2010)



TRANSMISSION MANUAL S6-650 6/1

Capacity: 5,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 105000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 50000 miles*

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

HYDRAULIC CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

POWER STEERING

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

FORD (USA) F-550 (SUPER DUTY) F-550 5.4 V8 SUPER DUTY (2008-2010)

**COOLING SYSTEM**

Capacity: 25,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	

Check every 6 months, change every 45000 miles/ 36 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	

Check every 6 months, change every 105000 miles/ 72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.