## FORD (USA) F-550 (SUPER DUTY) F-550 6.8 V10 SUPER DUTY 4X4 (2011-2016)



<b>ENGINE</b> Triton Capacity: 6,6 liter		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		
Change every 5000 miles/ 6 months		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		
Check every 1 months, change every 7500	) miles/ 6 months	

<b>DIFFERENTIAL FRONT</b> (4x4) Capacity: 2,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 150000 miles	'	

Capacity: 4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 105000 miles	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 50000 miles	

## FORD (USA) F-550 (SUPER DUTY) F-550 6.8 V10 SUPER DUTY 4X4 (2011-2016)



TRANSFERBOX Capacity: 1,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 150000 miles	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 60000 miles	

TRANSMISSION AUTOMATIC 5F Capacity: 16,6 liter	R110W 5/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	
Change every 60000 miles	'	'

TRANSMISSION AUTOMATIC 6R140(W) 6/1 Capacity: 15,8-17,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 4036	SP Matic 2032		
Change every 150000 miles			

_

## FORD (USA) F-550 (SUPER DUTY) F-550 6.8 V10 SUPER DUTY 4X4 (2011-2016)



POWER STEERING Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

COOLING SYSTEM Capacity: 25,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 6 months, change eve	ery 45000 miles/ 36 months	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Check every 6 months, change every 105000 miles/72 months