## **GINAF M SERIES M 3233-S.430 (6X4)** (1993-2001)



<b>ENGINE</b> XF 315 M Euro 2 Capacity: 29 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Armado Synth 5W-30	Dieselfleet CD+ 15W-40

DIFFERENTIAL REAR APS 16250/APS 16251	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube HS GL-5 80W-140	

HUB REDUCTIONS REAR	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube HS GL-5 80W-140	

RETARDER Voith 133 Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 10W-40	HDX 30	HDX 20W-20

Change every 100000 km/ 12 months

STEERING SYSTEM REAR AXLE EVS		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		
Change every 24 months	·	

## **GINAF M SERIES M 3233-S.430 (6X4)** (1993-2001)



TRANSMISSION MANUAL 16S 181 16/2 Capacity: 13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube GL-4 80W	Gearlube GL-4 80W-90

HYDRAULIC CAB TILT SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

HYDRAULIC SUSPENSION REAR AXLE HPVS / EVS		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		
Change every 24 months	'	

HYDRAULIC CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Change every 24 months	1	1

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 24 months	·

## **GINAF M SERIES M 3233-S.430 (6X4)** (1993-2001)



CENTRAL LUBRICATION SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gear Grease EP 00/000		

Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
GREASE POINTS/NIPPLES		

COOLING SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Change every 24 months	,	,

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.