IVECO FORD SUPERCARGO TECTOR SUPERCARGO TECTOR 180 E28 (2001-2008)



Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Normal		Moderate	
USE		CLIMATE	
ENGINE Iveco F4AE0681A*C Euro 3 Capacity: 10,8 liter			

DIFFERENTIAL REAR HYPOID Rockwell S167E		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140

TRANSMISSION MANUAL Iveco 2895.9 9/1 Capacity: 8,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90		

HYDRAULIC CAB TILT SYSTEM Capacity: 0,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
LHM +	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

IVECO FORD SUPERCARGO TECTOR SUPERCARGO TECTOR 180 E28 (2001-2008)



POWER STEERING ZF 8098	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
WHEEL BEARINGS FRONT OIL LUI	BRICATED Iveco 5871	

COOLING SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
	·	<u>'</u>	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.