

MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)



ENGINE AC-310/330 ASET
Capacity: 38 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

Change every 40000 km/ 600 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Armado Synth LSP 10W-40

PRODUCT RECOMMENDATION 2

Armado Synth 10W-40

PRODUCT RECOMMENDATION 3

Synfleet SHPD 10W-40

Change every 40000 km/ 600 hours

DIFFERENTIAL REAR 4x2 Mack RA23R
Capacity: 16,3 liter

USE	CLIMATE
Long distance	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Gearlube GL-5 80W-90

Change every 400000 km/ 24 months

USE	CLIMATE
Long distance, extended	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

Change every 800000 km/ 36 months

USE	CLIMATE
Vocational	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Gearlube GL-5 80W-90

Change every 64000 km/ 12 months/ 1200 hours

USE	CLIMATE
Vocational, extended	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

Change every 128000 km/ 12 months/ 1200 hours

DIFFERENTIAL REAR 4x2 Meritor RS23-161
Capacity: 17,6 liter

MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)



USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 8000 km/ 1 months, change every 40000 km/ 12 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140

Check every 8000 km/ 1 months, change every 40000 km/ 12 months

USE		CLIMATE
Long distance		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 40000 km, change every 160000 km/ 12 months

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140

Check every 40000 km, change every 160000 km/ 12 months

USE		CLIMATE
Long distance, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Check every 40000 km, change every 800000 km/ 48 months

USE		CLIMATE
Severe, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Check every 8000 km/ 1 months, change every 160000 km/ 24 months

DIFFERENTIAL REAR 4x2 Meritor RS23-186 Capacity: 22,4 liter

USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 8000 km/ 1 months, change every 40000 km/ 12 months

MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)



USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140

Check every 8000 km/ 1 months, change every 40000 km/ 12 months

USE		CLIMATE
Long distance		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 40000 km, change every 160000 km/ 12 months

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140

Check every 40000 km, change every 160000 km/ 12 months

USE		CLIMATE
Long distance, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Check every 40000 km, change every 800000 km/ 48 months

USE		CLIMATE
Severe, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Check every 8000 km/ 1 months, change every 160000 km/ 24 months

TRANSMISSION AUTOMATIC Allison 4000 HS 5/1

Capacity: 43 liter (+ PTO, deep sump), Capacity: 33 liter (+ PTO, shallow sump), Capacity: 40 liter (deep sump), Capacity: 30 liter (shallow sump)

USE		CLIMATE
Extended		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Change every 240000 km/ 48 months/ 4000 hours

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 40000 km/ 12 months/ 1000 hours

MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)



USE	CLIMATE
Severe (alternative)	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Matic 2032	ATF Almirol

Change every 20000 km/ 6 months/ 500 hours

USE	CLIMATE
Severe, 4 inch sump	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Matic 2032	

Change every 120000 km/ 36 months/ 3000 hours

USE	CLIMATE
Severe, 2 inch sump	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Matic 2032	

Change every 80000 km/ 24 months/ 2000 hours

TRANSMISSION AUTOMATIC Allison 4500 HS 5/1

Capacity: 43 liter (+ PTO, deep sump), Capacity: 33 liter (+ PTO, shallow sump), Capacity: 40 liter (deep sump), Capacity: 30 liter (shallow sump)

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Matic 2032	

Change every 240000 km/ 48 months/ 4000 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Matic 2032	ATF Almirol

Change every 40000 km/ 12 months/ 1000 hours

USE	CLIMATE
Severe (alternative)	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Matic 2032	ATF Almirol

Change every 20000 km/ 6 months/ 500 hours

USE	CLIMATE
Severe, 4 inch sump	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Matic 2032	

Change every 120000 km/ 36 months/ 3000 hours

MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)



USE		CLIMATE
Severe, 2 inch sump		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Change every 80000 km/ 24 months/ 2000 hours		

TRANSMISSION MANUAL Eaton-Fuller FR 10 10/2 Capacity: 11,1 liter		
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Change every 90000 km/ 12 months		

TRANSMISSION MANUAL Eaton-Fuller FRLO 10/2 Capacity: 12,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Change every 90000 km/ 12 months		

TRANSMISSION MANUAL Eaton-Fuller FRO 10/2 Capacity: 11 liter		
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Change every 90000 km/ 12 months		

TRANSMISSION MANUAL Eaton-Fuller RTO Autoshift 10/2 Capacity: 12 liter		
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Change every 90000 km/ 12 months		



MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)


TRANSMISSION MANUAL Eaton-Fuller RTO Ultrashift 10/2

Capacity: 12 liter

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 50

Change every 90000 km/ 12 months

TRANSMISSION MANUAL T-309 9/2

Capacity: 11,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Gearlube GL-5 80W-90

Change every 400000 km/ 24 months

USE	CLIMATE
Long distance	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

Change every 800000 km/ 36 months

USE	CLIMATE
Vocational	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Gearlube GL-5 80W-90

Change every 64000 km/ 12 months/ 1200 hours

USE	CLIMATE
Vocational, extended	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

Change every 128000 km/ 12 months/ 1200 hours

MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)

**TRANSMISSION MANUAL T-309LR 9/2**

Capacity: 11,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 400000 km/ 24 months

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 800000 km/ 36 months

USE		CLIMATE
Vocational		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 64000 km/ 12 months/ 1200 hours

USE		CLIMATE
Vocational, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 128000 km/ 12 months/ 1200 hours

MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)

**TRANSMISSION MANUAL T-310 10/2**

Capacity: 14,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 400000 km/ 24 months

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 800000 km/ 36 months

USE		CLIMATE
Vocational		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 64000 km/ 12 months/ 1200 hours

USE		CLIMATE
Vocational, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 128000 km/ 12 months/ 1200 hours

MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)


TRANSMISSION MANUAL T-310M 10/2

Capacity: 14,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 400000 km/ 24 months

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 800000 km/ 36 months

USE		CLIMATE
Vocational		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 64000 km/ 12 months/ 1200 hours

USE		CLIMATE
Vocational, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 128000 km/ 12 months/ 1200 hours

MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)


TRANSMISSION MANUAL T-310ME 10/2

Capacity: 14,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 400000 km/ 24 months

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 800000 km/ 36 months

USE		CLIMATE
Vocational		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 64000 km/ 12 months/ 1200 hours

USE		CLIMATE
Vocational, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 128000 km/ 12 months/ 1200 hours

MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)

**TRANSMISSION MANUAL T-313 L 13/2**

Capacity: 14,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 400000 km/ 24 months

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 800000 km/ 36 months

USE		CLIMATE
Vocational		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 64000 km/ 12 months/ 1200 hours

USE		CLIMATE
Vocational, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 128000 km/ 12 months/ 1200 hours

MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)


TRANSMISSION MANUAL T-313LR 13/2

Capacity: 14,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 400000 km/ 24 months

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 800000 km/ 36 months

USE		CLIMATE
Vocational		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 64000 km/ 12 months/ 1200 hours

USE		CLIMATE
Vocational, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 128000 km/ 12 months/ 1200 hours

MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)

**TRANSMISSION MANUAL T-318 L 18/3**

Capacity: 14,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 400000 km/ 24 months

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 800000 km/ 36 months

USE		CLIMATE
Vocational		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 64000 km/ 12 months/ 1200 hours

USE		CLIMATE
Vocational, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 128000 km/ 12 months/ 1200 hours

MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)

**TRANSMISSION MANUAL T-318L21 18/3**

Capacity: 14,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 400000 km/ 24 months

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 800000 km/ 36 months

USE		CLIMATE
Vocational		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 64000 km/ 12 months/ 1200 hours

USE		CLIMATE
Vocational, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 128000 km/ 12 months/ 1200 hours

MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)



TRANSMISSION MANUAL T-318LR 18/3

Capacity: 14,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 400000 km/ 24 months

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 800000 km/ 36 months

USE		CLIMATE
Vocational		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 64000 km/ 12 months/ 1200 hours

USE		CLIMATE
Vocational, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 128000 km/ 12 months/ 1200 hours

HYDRAULIC SYSTEM CAB TILT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

MACK CH/CHN SERIES CHN602 AC-310/330 ASET (2002-2008)



POWER STEERING

Capacity: 1,9-3,8 liter

USE		CLIMATE
->2005		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet CD+ 15W-40		

USE		CLIMATE
->2005		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP 10W-40	Armado Synth 10W-40	Synfleet SHPD 10W-40

USE		CLIMATE
2005->		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

GREASE POINTS/NIPPLES CHASSIS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 40000 km/ 600 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 34 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 40000 km/ 600 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.