

# MACK MACK MP ENGINES MP7/MP8/MP10 MP10 EPA 10 (STANDARD OIL PAN) (2010-2016)



**ENGINE** MP10  
Capacity: 42 liter

USE	CLIMATE
Medium duty, fuel consumption > 6.0 MPG, large oil sump	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth MSP 5W-40</b>

*Change every 80000 km*

USE	CLIMATE
Medium duty, fuel consumption > 6.0 MPG, normal oil sump	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth MSP 5W-40</b>

*Change every 56000 km*

USE	CLIMATE
Heavy duty, fuel consumption 4.7 - 6.0 MPG, large oil sump	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth MSP 5W-40</b>

*Change every 56000 km*

USE	CLIMATE
Heavy duty, fuel consumption 4.7 - 6.0 MPG, normal oil sump	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth MSP 5W-40</b>

*Change every 40000 km*

USE	CLIMATE
Severe, fuel consumption 3.7 - 4.7 MPG, large oil sump	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth MSP 5W-40</b>

*Change every 40000 km*

USE	CLIMATE
Severe, fuel consumption 3.7 - 4.7 MPG, normal oil sump	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth MSP 5W-40</b>

*Change every 24000 km*

USE	CLIMATE
Very severe, fuel consumption 2.0 - 3.7 MPG, large oil sump	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth MSP 5W-40</b>

*Change every 24000 km*

# MACK MACK MP ENGINES MP7/MP8/MP10 MP10 EPA 10 (STANDARD OIL PAN) (2010-2016)



USE		CLIMATE
Very severe, fuel consumption 2.0 - 3.7 MPG, normal oil sump		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth MSP 5W-40</b>
<i>Change every 16000 km</i>		

COOLING SYSTEM		
Capacity: 62,5 liter (with automatic transmission), Capacity: 53 liter (with manual transmission)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	
<i>Check every 6 months</i>		

SELECTIVE CATALYTIC REDUCTION SYSTEM (SCR)
We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*