

MACK MACK MP ENGINES MP7/MP8/MP10

MP7 (2002-2010)



ENGINE MP7
Capacity: 34 liter

USE	CLIMATE
Long distance	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

Change every 24000 km/ 250 hours

USE	CLIMATE
Long distance	Arctic

PRODUCT RECOMMENDATION 1

Armado Synth LSP 10W-40

PRODUCT RECOMMENDATION 2

Armado Synth 10W-40

PRODUCT RECOMMENDATION 3

Synfleet SHPD 10W-40

Change every 24000 km/ 250 hours

USE	CLIMATE
Regional	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

Change every 12000 km/ 45 days/ 150 hours

USE	CLIMATE
Regional	Arctic

PRODUCT RECOMMENDATION 1

Armado Synth LSP 10W-40

PRODUCT RECOMMENDATION 2

Armado Synth 10W-40

PRODUCT RECOMMENDATION 3

Synfleet SHPD 10W-40

Change every 12000 km/ 45 days/ 150 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.