

AND AFTER)

| ENGINE 414 (D2866 LF31/EDC) Capacity: 43 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 40 | Multifleet SCD 30 | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Armado Synth 10W-40 | Synfleet SHPD 10W-40 | Armado Synth 5W-30 |

| DIFFERENTIAL REAR MAN HY-1 Capacity: 15,7 liter | 3110 | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear TDL 75W-90 | Gearlube GL-5 80W-90 |

| TRANSMISSION MANUAL Eaton RSTO 12316 A 16/2 Capacity: 12,3 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear MT/LD 75W-80 | Syngear TDL 75W-90 |

| HYDRAULIC CAB TILT SYSTEM | | |
|---------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 15 | | |
| | | |

| HYDRAULIC CLUTCH SYSTEM | | |
|--------------------------|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 5.1 | | |
| Change every 24 months | · | |



AND AFTER)

| POWER STEERING Capacity: 4 liter | | |
|-------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Matic 2032 | ATF Almirol | ATF Dexron II-D |

| CENTRAL LUBRICATION SYSTEM BEKA-MAX | | |
|-------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| CENTRAL LUBRICATION SYSTEM Groeneveld | | | |
|---------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Gear Grease EP 0 | Gear Grease EP 00/000 | | |

| CENTRAL LUBRICATION SYSTEM GREASE Vogel | | |
|---|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Grease EP 00/000 | | |

| CENTRAL LUBRICATION SYSTEM OIL Vogel | | |
|--------------------------------------|--------------------------|--------------------------|
| Normal CLIMATE Moderate | | |
| | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Armado Synth 10W-40 | Synfleet SHPD 10W-40 | Armado Synth 5W-30 |

| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal | | Moderate |
| USE | | CLIMATE |
| GREASE POINTS/NIPPLES | | |



AND AFTER)

| GREASE POINTS/NIPPLES PROPELLER SHAFT JOINTS | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| GREASE POINTS/NIPPLES WHEEL BEARINGS REAR LEADING V9-75L(FVL) | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| GREASE POINTS/NIPPLES WHEEL BEARINGS REAR TRAILING MAN H9-75 (FNL/FNLL) | | |
|---|--------------------------|--|
| USE CLIMATE | | |
| | Moderate | |
| PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | |
| | PRODUCT RECOMMENDATION 2 | |

| GREASE POINTS/NIPPLES WHEEL BEARINGS REAR TRAILING MAN HN9-75L(FNL-G/FNLL-G) | | |
|--|--------------------------|--|
| | CLIMATE | |
| | Moderate | |
| PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | |
| | PRODUCT RECOMMENDATION 2 | |

| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
|----------------------------|--------------------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal | | Moderate |
| USE | | CLIMATE |
| GREASE POINTS/NIPPLES WHEE | EL BEARINGS REAR TRAILING Sauer AR31 | 3-RZM 11242 |



AND AFTER)

| WHEEL BEARINGS REAR OIL LUBRICATED Capacity: 0,7 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear TDL 75W-90 | Gearlube GL-5 80W-90 |

| COOLING SYSTEM | | | |
|--------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant -38 Organic NF | Coolant -26 | | |

| RETARDER | | |
|--------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 30 | Multifleet SCD 20W-20 | |
| | I | I |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.