## MAN LE-C LE-C 12.185 LC/LLC (2003-2006)



| <b>ENGINE</b> D 0834 LFL03 Euro 3<br>Capacity: 16,5 liter |                          |                          |
|---|--------------------------|--------------------------|
| USE   |                          | CLIMATE                  |
| Normal  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                                  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Armado Synth LSP Ultra 10W-40                             | Armado Synth LSP 10W-40  | Armado Synth 10W-40      |

Check every 6 months

| <b>DIFFERENTIAL REAR</b> HY-0855<br>Capacity: 11,8 liter |                          |                          |
|--|--------------------------|--------------------------|
| USE  |                          | CLIMATE                  |
| Normal   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                                 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011   | Syngear TDL 75W-90       | Gearlube GL-5 80W-90     |

Check every 6 months

| HUB REDUCTIONS REAR HY-085<br>Capacity: 0,5 liter | 5                        |                          |
|---|--------------------------|--------------------------|
| USE   |                          | CLIMATE                  |
| Normal  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                          | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011                                      | Syngear TDL 75W-90       | Gearlube GL-5 80W-90     |

Check every 6 months

| TRANSMISSION MANUAL ZF 6S-850 6<br>Capacity: 7,5 liter | /1                       |                          |
|--|--------------------------|--------------------------|
| USE  |                          | CLIMATE                  |
| Normal   |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1                               |                          |                          |
| Multifleet SCD 30                                      |                          |                          |
| Check every 6 months                                   |                          |                          |
| USE  |                          | CLIMATE                  |
| Normal   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                               | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011   | Syngear MT/LD 75W-80     | Syngear TDL 75W-90       |

Check every 6 months

## MAN LE-C LE-C 12.185 LC/LLC (2003-2006)



| IYDRAULIC CAB TILT SYSTEM |  |          |
|---------------------------|--|----------|
| USE                       |  | CLIMATE  |
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| Perlus H 15               |  |          |
|                           |  |          |

Check every 6 months

| HYDRAULIC CLUTCH SYSTEM  |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Drauliquid DOT 5.1       |          |
|                          |          |

Check every 6 months

| POWER STEERING           |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Matic 2032            | ATF Almirol              | ATF Dexron II-D          |
|                          |                          |                          |

Check every 6 months

|                          |                          | 1        |
|--------------------------|--------------------------|----------|
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |          |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| Normal                   |                          | Moderate |
| USE                      |                          | CLIMATE  |
| GREASE POINTS/NIPPLES    |                          |          |

Check every 6 months

| COOLING SYSTEM           |                          |          |
|--------------------------|--------------------------|----------|
| USE                      |                          | CLIMATE  |
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| Coolant SP 15+           | Coolant SP 12            |          |
| Check every 6 months     |                          | ·        |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.