

**MAN LE-C LE-C 9.220 BB/BL (2004-2006)**

**ENGINE** D 0836 LFL02/Euro 3  
Capacity: 21,5 liter

USE	CLIMATE
Long distance, green dipstick ring	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth LSP 10W-40</b>	<b>Armado Synth 10W-40</b>

*Change every 60000 km/ 12 months*

USE	CLIMATE
Long distance, red dipstick ring	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth LSP 10W-40</b>	<b>Armado Synth 10W-40</b>

*Change every 45000 km/ 12 months*

USE	CLIMATE
Short distance, green dipstick ring	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth LSP 10W-40</b>	<b>Armado Synth 10W-40</b>

*Change every 45000 km/ 12 months*

USE	CLIMATE
Short distance, red dipstick ring	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth LSP 10W-40</b>	<b>Armado Synth 10W-40</b>

*Change every 30000 km/ 12 months*

**DIFFERENTIAL REAR** HY-0855  
Capacity: 12,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	

*Change every 320000 km/ 36 months*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 180000 km/ 36 months*

**MAN LE-C LE-C 9.220 BB/BL (2004-2006)****TRANSMISSION MANUAL ZF 6S-850 6/1**

Capacity: 7,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Syngear MT/LD 75W-80</b>		

*Change every 320000 km/ 36 months*

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>SP Gear 5015</b>	<b>Syngear MT/LD 75W-80</b>

*Change every 180000 km/ 36 months*

HYDRAULIC CAB TILT SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 15</b>		

*Check every 60000 km/ 12 months*

HYDRAULIC CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 5.1</b>		

*Check every 60000 km/ 12 months*

POWER STEERING ZF 8095		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>

*Check every 60000 km/ 12 months*

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>

*Check every 60000 km/ 12 months*

**MAN LE-C LE-C 9.220 BB/BL (2004-2006)****COOLING SYSTEM**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12***Change every 500000 km/ 48 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*