

MERCEDES-BENZ (EU) ACTROS ACTROS

1855 L/LS (4X2) EURO 5 (2009-2013)



ENGINE OM502LA IV
Capacity: 38 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

DIFFERENTIAL REAR HYPOID HL 8
Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Check every 12 months

TRANSMISSION MANUAL G240-16 16/2
Capacity: 14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Syngear HS 75W-90		

Check every 12 months

HYDRAULIC ACTUATION GEARBOX

USE		CLIMATE
Black reservoir cap		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Check every 12 months, change every 36 months

USE		CLIMATE
Green reservoir cap		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

MERCEDES-BENZ (EU) ACTROS ACTROS

1855 L/LS (4X2) EURO 5 (2009-2013)



HYDRAULIC CAB TILT SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

Check every 12 months

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Black reservoir cap		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Check every 12 months, change every 36 months

USE		CLIMATE
Green reservoir cap		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4026	SP Matic 2032	ATF-A

Check every 12 months

GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Check every 12 months

WHEEL BEARINGS FRONT VL4

We are unable to give a standard recommendation for this component. Please contact our service department.

MERCEDES-BENZ (EU) ACTROS ACTROS

1855 L/LS (4X2) EURO 5 (2009-2013)

**COOLING SYSTEM**

Capacity: 45 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Check every 12 months, change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.