

MERCEDES-BENZ (EU) ATEGO EURO 3

ATEGO 2528 LL 6X2 EURO 3 (2001-2006)



ENGINE OM906LA III/4; Euro 3
Capacity: 29,3 liter

| | | |
|----------------------|--|----------------------------|
| USE Normal | | CLIMATE Moderate |
|----------------------|--|----------------------------|

| | | |
|--|---|---|
| PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 5W-30 | PRODUCT RECOMMENDATION 2 Armado Synth LSP Ultra 10W-40 | PRODUCT RECOMMENDATION 3 Armado Synth LSP 10W-40 |
|--|---|---|

Change every 12 months

DIFFERENTIAL REAR

| | | |
|----------------------|--|----------------------------|
| USE Normal | | CLIMATE Moderate |
|----------------------|--|----------------------------|

| | | |
|--|--|--|
| PRODUCT RECOMMENDATION 1 SP Gear 1011 | PRODUCT RECOMMENDATION 2 Syngear TDL 75W-90 | PRODUCT RECOMMENDATION 3 Gearlube GL-5 80W-90 |
|--|--|--|

RETARDER Voith R 115
Capacity: 5,4 liter

| | | |
|----------------------|--|----------------------------|
| USE Normal | | CLIMATE Tropical |
|----------------------|--|----------------------------|

| | | |
|---|--|--|
| PRODUCT RECOMMENDATION 1 Multifleet SCD 30 | | |
|---|--|--|

| | | |
|----------------------|--|----------------------------|
| USE Normal | | CLIMATE Moderate |
|----------------------|--|----------------------------|

| | | |
|---|--|--|
| PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 | PRODUCT RECOMMENDATION 2 Multifleet SCD 10W | |
|---|--|--|

TRANSMISSION AUTOMATIC Allison WT-MD 3060 6/1

| | | |
|----------------------|--|----------------------------|
| USE Normal | | CLIMATE Moderate |
|----------------------|--|----------------------------|

| | | |
|---|---|---|
| PRODUCT RECOMMENDATION 1 SP Matic 4026 | PRODUCT RECOMMENDATION 2 SP Matic 2032 | PRODUCT RECOMMENDATION 3 ATF Almirol |
|---|---|---|

Change every 60000 km

TRANSMISSION MANUAL MB G 100-12 12/1

| | | |
|----------------------|--|----------------------------|
| USE Normal | | CLIMATE Moderate |
|----------------------|--|----------------------------|

| | | |
|---|---|--|
| PRODUCT RECOMMENDATION 1 Syngear HS 75W-90 | PRODUCT RECOMMENDATION 2 Gearlube GL-4 80W | |
|---|---|--|

MERCEDES-BENZ (EU) ATEGO EURO 3

ATEGO 2528 LL 6X2 EURO 3 (2001-2006)



HYDRAULIC ACTUATION GEARBOX

| USE | CLIMATE |
|---------------------|----------|
| Black reservoir cap | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Drauliquid-S DOT 4 | | |

Change every 36 months

| USE | CLIMATE |
|---------------------|----------|
| Green reservoir cap | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Fluid 3013 | | |

HYDRAULIC CAB TILT SYSTEM

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Perlus H 15 | | |

HYDRAULIC SYSTEM

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Perlus H 15 | | |

HYDRAULIC CLUTCH SYSTEM

| USE | CLIMATE |
|---------------------|----------|
| Black reservoir cap | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Drauliquid-S DOT 4 | | |

Change every 36 months

| USE | CLIMATE |
|---------------------|----------|
| Green reservoir cap | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Fluid 3013 | | |

MERCEDES-BENZ (EU) ATEGO EURO 3

ATEGO 2528 LL 6X2 EURO 3 (2001-2006)



POWER STEERING

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Matic 4026 | SP Matic 2032 | |

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

We are unable to give a standard recommendation for this component. Please contact our service department.

WHEEL BEARINGS TRAILING AXLE NR4

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 23 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 11 | |

Change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.