

MERCEDES-BENZ (EU) ATEGO EURO 4

ATEGO 1224 LL (2006-2010)



ENGINE OM906LA IV
Capacity: 29 liter

USE		CLIMATE
Euro 4+5		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

USE		CLIMATE
Euro 4+5 + DPF		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

DIFFERENTIAL REAR HYPOID MB HL2
Capacity: 5,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 24 months

USE		CLIMATE
Full synthetic product		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 36 months

TRANSMISSION MANUAL G 56-6 6/1
Capacity: 6,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W	Gearlube GL-4 80W-90	

Change every 36 months

MERCEDES-BENZ (EU) ATEGO EURO 4

ATEGO 1224 LL (2006-2010)


TRANSMISSION MANUAL G 60-6 6/1

Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W	Gearlube GL-4 80W-90	

Change every 36 months
TRANSMISSION MANUAL G100-12 12/1

Capacity: 12 liter, Capacity: 13 liter (+ oil cooler)

USE	CLIMATE
With oil cooler	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Syngear HS 75W-90	Gearlube GL-4 80W	Gearlube GL-4 80W-90

Change every 36 months

USE	CLIMATE
Without oil cooler	Moderate

PRODUCT RECOMMENDATION 1		
Syngear HS 75W-90		

Change every 60 months
TRANSMISSION MANUAL MB G 85-6 6/1

Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W	Gearlube GL-4 80W-90	

Change every 36 months

MERCEDES-BENZ (EU) ATEGO EURO 4

ATEGO 1224 LL (2006-2010)


TRANSMISSION MANUAL ZF S5-42 (710.62) 5/1

Capacity: 3,2 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90*Change every 36 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W*Change every 36 months*
TRANSMISSION MANUAL ZF S9-75 9/1

Capacity: 10,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Syngear HS 75W-90

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W

PRODUCT RECOMMENDATION 3

Gearlube GL-4 80W-90*Change every 36 months*
HYDRAULIC ACTUATION GEARBOX

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013*Change every 36 months*
HYDRAULIC CAB TILT SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 15

MERCEDES-BENZ (EU) ATEGO EURO 4

ATEGO 1224 LL (2006-2010)



HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		
<i>Check every 12 months</i>		

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Black reservoir cap		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		
<i>Change every 36 months</i>		

USE		CLIMATE
Green reservoir cap		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
<i>Change every 24 months</i>		

MERCEDES-BENZ (EU) ATEGO EURO 4

ATEGO 1224 LL (2006-2010)

**COOLING SYSTEM**

Capacity: 23 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11*Change every 36 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.