

MERCEDES-BENZ (EU) SK 645 --> 649, 655 -- > 659 SK 2648 (6X2) (1988-1992)



ENGINE OM442LA
Capacity: 27 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Dieselfleet MSP 15W-40

PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Change every 45000 km

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Armado Synth LSP Ultra 5W-30

PRODUCT RECOMMENDATION 2
Armado Synth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 3
Armado Synth LSP 10W-40

Change every 45000 km

DIFFERENTIAL REAR LEADING HD 7 + HL 7
Capacity: 8 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
SP Gear 1011

PRODUCT RECOMMENDATION 2
Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90

Change every 90000 km

DIFFERENTIAL REAR TRAILING HD 7 + HL 7
Capacity: 8 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
SP Gear 1011

PRODUCT RECOMMENDATION 2
Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90

Change every 90000 km

HUB REDUCTIONS REAR HL 7/07 DL-11,5 (L/LS)
Capacity: 3,25 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
SP Gear 1011

PRODUCT RECOMMENDATION 2
Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90

Change every 90000 km

MERCEDES-BENZ (EU) SK 645 --> 649, 655 -- > 659 SK 2648 (6X2) (1988-1992)

**POWER DIVIDER**

Capacity: 2,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Gearlube GL-5 80W-90*Change every 90000 km***RETARDER** Voith 130/132

Capacity: 8,5 liter

USE

Normal

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 90000 km*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20

PRODUCT RECOMMENDATION 2

Multifleet SCD 10W*Change every 90000 km***TRANSMISSION MANUAL** ZF 16S-190 EPS 16/1

Capacity: 16,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Syngear HS 75W-90

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W

PRODUCT RECOMMENDATION 3

Gearlube GL-4 80W-90*Change every 90000 km***POWER STEERING**

Capacity: 3,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

PRODUCT RECOMMENDATION 2

SP Matic 2032**CENTRAL LUBRICATION SYSTEM**

Capacity: 2,7 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

MERCEDES-BENZ (EU) SK 645 --> 649, 655 -- > 659 SK 2648 (6X2) (1988-1992)



GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
<i>Change every 12 months</i>		

COOLING SYSTEM

Capacity: 46 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 11	
<i>Change every 12 months</i>		

OIL BATH AIR CLEANER

Capacity: 5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet MSP 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.