

# MERITOR SINGLE REDUCTION AXLES - STEERED FDS FDS-1600


**DIFFERENTIAL STEERED AXLE**

Capacity: 3,3 liter

USE		CLIMATE
Normal		Mediterranean

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140**

## PRODUCT RECOMMENDATION 2

**Unigear LS GL-3/GL-5 85W-140***Check every 4800 km/ 1 months, change every 160000 km*

USE		CLIMATE
Normal		Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140**

## PRODUCT RECOMMENDATION 2

**SP Gear 1011**

## PRODUCT RECOMMENDATION 3

**Syngear TDL 75W-90***Check every 4800 km/ 1 months, change every 160000 km*

USE		CLIMATE
Normal		Cold

## PRODUCT RECOMMENDATION 1

**SP Gear 5015***Check every 4800 km/ 1 months, change every 160000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.