## MERITOR SINGLE REDUCTION AXLES - TANDEM AXLES ST-270/280, RT-, RP-52-380



DIFFERENTIAL REAR LEADING Capacity: 26 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 4800 km/ 1 months, cha	nge every 160000 km	
JSE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90
Check every 4800 km/ 1 months, cha	nge every 160000 km	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Check every 4800 km/ 1 months, cha	nge every 160000 km	
DIFFERENTIAL REAR TRAILING		
Capacity: 26 liter		
USE 		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 4800 km/ 1 months, cha	nge every 160000 km	
USE		CLIMATE

Check every 4800 km/1 months, change every 160000 km

USE	CLIMATE
Normal	Cold
PRODUCT RECOMMENDATION 1	
SP Gear 5015	

PRODUCT RECOMMENDATION 2

**SP Gear 1011** 

Check every 4800 km/ 1 months, change every 160000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Normal

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Moderate

PRODUCT RECOMMENDATION 3

Syngear TDL 75W-90