MERITOR SINGLE REDUCTION AXLES C-100



DIFFERENTIAL REAR Capacity: 5,9 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 4800 km/ 1 months, change every 160000 km		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90
Check every 4800 km/ 1 months, change every 160000 km		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Check every 4800 km/ 1 months, change every 160000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.