

# NISSAN (EU) ATLEON ATLEON.140 (UNTIL VIN 514110) (2000-2002)



**ENGINE** B4-40 Ti  
Capacity: 8,8 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 50</b>	<b>Multifleet SCD 40</b>	

*Change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

*Change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Change every 20000 km/ 12 months*

**DIFFERENTIAL REAR**  
Capacity: 6 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Gearlube GL-5 85W-140</b>		

*Check every 20000 km, change every 40000 km/ 24 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>SP Gear 5015</b>	<b>SP Gear 1071</b>

*Check every 20000 km, change every 40000 km/ 24 months*

# NISSAN (EU) ATLEON ATLEON.140 (UNTIL VIN 514110) (2000-2002)



## DIFFERENTIAL REAR LIMITED SLIP

Capacity: 6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

Check every 20000 km, change every 40000 km/ 24 months

## TRANSMISSION MANUAL

Capacity: 3,2 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Unigear LS GL-3/GL-5 85W-140</b>		

Check every 20000 km, change every 40000 km/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>SP Gear 5015</b>	<b>Syngear TDL 75W-90</b>

Check every 20000 km, change every 40000 km/ 24 months

## HYDRAULIC BRAKE SYSTEM

Capacity: 1,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

Change every 40000 km/ 48 months

## HYDRAULIC CLUTCH SYSTEM

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

Change every 40000 km/ 48 months

# NISSAN (EU) ATLEON ATLEON.140 (UNTIL VIN 514110) (2000-2002)



## POWER STEERING

Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D**

Change every 100000 km/ 60 months

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

Change every 20000 km/ 12 months

## GREASE POINTS/NIPPLES HUB UNIT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

Change every 40000 km/ 48 months

## COOLING SYSTEM

Capacity: 18,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26**

Change every 40000 km/ 48 months

## AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*