PRODUCT RECOMMENDATION

PETERBILT VOCATIONAL TRUCKS 320
CUMMINS ISL G (2009-2013)

ENGINE Cummins Westport ISL G
Capacity: 27,6 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION AUTOMATIC Allison

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 15000 miles, change every 25000 miles

TRANSMISSION MANUAL Fuller

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Multifleet SCD 50		

Check every 15000 miles, change every 50000 miles

HYDRAULIC HOOD TILT SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

POWER STEERING Sheppard

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	**ATF Almirol**	**ATF Dexron II-D**

Check every 15000 miles, change every 240000 miles/ 24 months

POWER STEERING TRW

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	**ATF Almirol**	**ATF Dexron II-D**

Check every 15000 miles, change every 240000 miles/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

PETERBILT VOCATIONAL TRUCKS 320 CUMMINS ISL G (2009-2013)

WHEEL BEARINGS DRIVEN HUBS OIL LUBRICATED Eaton/Dana
Capacity: 0,92 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

WHEEL BEARINGS NON DRIVEN HUBS OIL LUBRICATED LMS Eaton/Dana
Capacity: 0,27 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

WHEEL BEARINGS NON DRIVEN HUBS OIL LUBRICATED NON-LMS + OUTRUNNER SEALS Eaton/Dana
Capacity: 0,3-0,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

WHEEL BEARINGS NON DRIVEN HUBS OIL LUBRICATED NON-LMS + STANDARD SEALS Eaton/Dana
Capacity: 0,3-0,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM
Capacity: 12,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant SP 12 EVO**

Change every 60000 miles/ 24 months/ 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367