

PETERBILT VOCATIONAL TRUCKS 320

CUMMINS ISX15 (2009-2013)



ENGINE Cummins ISX
Capacity: 52,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Change every 15000 miles/ 6 months/ 400 hours

TRANSMISSION AUTOMATIC Allison

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 15000 miles, change every 25000 miles

TRANSMISSION MANUAL Fuller

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Multifleet SCD 50		

Check every 15000 miles, change every 50000 miles

HYDRAULIC HOOD TILT SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

POWER STEERING Sheppard

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 15000 miles, change every 240000 miles/ 24 months

POWER STEERING TRW

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 15000 miles, change every 240000 miles/ 24 months

PETERBILT VOCATIONAL TRUCKS 320

CUMMINS ISX15 (2009-2013)


WHEEL BEARINGS DRIVEN HUBS OIL LUBRICATED Eaton/Dana

Capacity: 0,92 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

WHEEL BEARINGS NON DRIVEN HUBS OIL LUBRICATED LMS Eaton/Dana

Capacity: 0,27 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

WHEEL BEARINGS NON DRIVEN HUBS OIL LUBRICATED NON-LMS + OUTFITTER SEALS Eaton/Dana

Capacity: 0,3-0,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

WHEEL BEARINGS NON DRIVEN HUBS OIL LUBRICATED NON-LMS + STANDARD SEALS Eaton/Dana

Capacity: 0,3-0,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant SP 12 EVO

Check every 15000 miles/ 6 months, change every 250000 miles/ 24 months/ 6000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.