## PETERBILT REGIONAL HAUL TRUCKS 325 PACCAR PX-6 (2010-2013)



ENGINE Paccar PX-6		
Capacity: 16,7 liter		
USE		CLIMATE
Refuse truck, mixer, dump truck: ave	erage speed > 25 mph	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40
Change every 12000 miles/ 6 months/ 500	) hours	
USE		CLIMATE
Refuse truck, mixer, dump truck: ave	erage speed 20 - 25 mph	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40
Change every 9000 miles/ 6 months/ 500	hours	
USE		CLIMATE
Refuse truck, mixer, dump truck: ave	erage speed 15 - 20 mph	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40
Change every 8500 miles/ 6 months/ 500	hours	
USE		CLIMATE
Refuse truck, mixer, dump truck: ave	erage speed 10 - 15 mph	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40
Change every 6000 miles/ 6 months/ 500	hours	
USE		CLIMATE
Refuse truck, mixer, dump truck: ave	erage speed < 10 mph	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40
Change every 3000 miles/ 6 months/ 500	hours	
USE		CLIMATE
Fuel economy > 7 MPG and GVW <	: 46000 lbs	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40
Change every 15000 miles/ 6 months/ 500	) hours	
USE		CLIMATE
Fuel economy < 7 MPG or dusty are	eas or idle time > 40% or gvw >	Moderate
46000 lbs		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40
Change every 9000 miles/ 6 months/ 500	hours	

KROON-OIL B.V. Postbus 149 7600 AC Almelo

## PETERBILT REGIONAL HAUL TRUCKS 325 PACCAR PX-6 (2010-2013)



DIFFERENTIAL Eaton/Dana		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 15000 miles, change every 500000 miles

TRANSMISSION AUTOMATIC Allison		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
	5000	

Check every 15000 miles, change every 25000 miles

TRANSMISSION MANUAL Fuller		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 50		
01 1 45000 11 1	2000 11	

Check every 15000 miles, change every 50000 miles

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Chack overy 7500 miles, change overy 600	100 miles/6 months	

Check every 7500 miles, change every 60000 miles/ 6 months

## PETERBILT REGIONAL HAUL TRUCKS 325 PACCAR PX-6 (2010-2013)



Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Off-road use		Moderate
USE		CLIMATE
Change every 750000 miles/ 72 mo	nths/ 22000 hours	
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
On-road use		Moderate
USE		CLIMATE
COOLING SYSTEM Capacity: 11,5 liter (Engine only)		

Change every 96 months/ 15000 hours

## SELECTIVE CATHALYTIC REDUCTION SYSTEM (SCR)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.