

PETERBILT REGIONAL HAUL TRUCKS 337

PACCAR PX-6 (2010-2013)



ENGINE Paccar PX-6
Capacity: 16,7 liter

USE	CLIMATE
Refuse truck, mixer, dump truck: average speed > 25 mph	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Change every 12000 miles/ 6 months/ 500 hours

USE	CLIMATE
Refuse truck, mixer, dump truck: average speed 20 - 25 mph	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Change every 9000 miles/ 6 months/ 500 hours

USE	CLIMATE
Refuse truck, mixer, dump truck: average speed 15 - 20 mph	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Change every 8500 miles/ 6 months/ 500 hours

USE	CLIMATE
Refuse truck, mixer, dump truck: average speed 10 - 15 mph	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Change every 6000 miles/ 6 months/ 500 hours

USE	CLIMATE
Refuse truck, mixer, dump truck: average speed < 10 mph	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Change every 3000 miles/ 6 months/ 500 hours

USE	CLIMATE
Fuel economy > 7 MPG and GVW < 46000 lbs	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Change every 15000 miles/ 6 months/ 500 hours

USE	CLIMATE
Fuel economy < 7 MPG or dusty areas or idle time > 40% or gvw > 46000 lbs	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Change every 9000 miles/ 6 months/ 500 hours

PETERBILT REGIONAL HAUL TRUCKS 337

PACCAR PX-6 (2010-2013)

**DIFFERENTIAL** Eaton/Dana

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Check every 15000 miles, change every 50000 miles</i>		

TRANSMISSION AUTOMATIC Allison

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
<i>Check every 15000 miles, change every 25000 miles</i>		

TRANSMISSION MANUAL Fuller

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 50		
<i>Check every 15000 miles, change every 50000 miles</i>		

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
<i>Check every 7500 miles, change every 60000 miles/ 6 months</i>		

PETERBILT REGIONAL HAUL TRUCKS 337

PACCAR PX-6 (2010-2013)



COOLING SYSTEM

Capacity: 11,5 liter (Engine only)

USE		CLIMATE
On-road use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 750000 miles/ 72 months/ 22000 hours

USE		CLIMATE
Off-road use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 96 months/ 15000 hours

SELECTIVE CATHALYTIC REDUCTION SYSTEM (SCR)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.