

PETERBILT REGIONAL HAUL TRUCKS 337

PACCAR PX-9 (2013-2016)

**ENGINE** Paccar PX-9

Capacity: 26,5 liter (High capacity oil sump), Capacity: 22,7 liter (standard oil sump), Capacity: 25,6 liter (Standard oil sump with cylinder block stiffener plate), Filter capacity: 3,78 liter

USE

Average vehicle speed > 40 mph

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Armado Synth LSP Ultra 5W-30****PRODUCT RECOMMENDATION 2****Armado Synth LSP Ultra 10W-40****PRODUCT RECOMMENDATION 3****Armado Synth MSP 5W-40**

Change every 20000 miles/ 12 months/ 500 hours

USE

Average vehicle speed 30 - 40 mph

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Armado Synth LSP Ultra 5W-30****PRODUCT RECOMMENDATION 2****Armado Synth LSP Ultra 10W-40****PRODUCT RECOMMENDATION 3****Armado Synth MSP 5W-40**

Change every 15000 miles/ 6 months/ 500 hours

USE

Average vehicle speed 25 - 30 mph

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Armado Synth LSP Ultra 5W-30****PRODUCT RECOMMENDATION 2****Armado Synth LSP Ultra 10W-40****PRODUCT RECOMMENDATION 3****Armado Synth MSP 5W-40**

Change every 12000 miles/ 6 months/ 500 hours

USE

Average vehicle speed 20 - 25 mph

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Armado Synth LSP Ultra 5W-30****PRODUCT RECOMMENDATION 2****Armado Synth LSP Ultra 10W-40****PRODUCT RECOMMENDATION 3****Armado Synth MSP 5W-40**

Change every 10500 miles/ 6 months/ 500 hours

USE

Average vehicle speed 15 - 20 mph

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Armado Synth LSP Ultra 5W-30****PRODUCT RECOMMENDATION 2****Armado Synth LSP Ultra 10W-40****PRODUCT RECOMMENDATION 3****Armado Synth MSP 5W-40**

Change every 8500 miles/ 6 months/ 500 hours

USE

Average vehicle speed 10 - 15 mph

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Armado Synth LSP Ultra 5W-30****PRODUCT RECOMMENDATION 2****Armado Synth LSP Ultra 10W-40****PRODUCT RECOMMENDATION 3****Armado Synth MSP 5W-40**

Change every 6000 miles/ 6 months/ 500 hours

USE

Average vehicle speed 5 - 10 mph

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Armado Synth LSP Ultra 5W-30****PRODUCT RECOMMENDATION 2****Armado Synth LSP Ultra 10W-40****PRODUCT RECOMMENDATION 3****Armado Synth MSP 5W-40**

Change every 4000 miles/ 6 months/ 500 hours

PETERBILT REGIONAL HAUL TRUCKS 337

PACCAR PX-9 (2013-2016)



USE		CLIMATE
Average vehicle speed < 5 mph		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40
<i>Change every 1500 miles/ 6 months/ 500 hours</i>		

DIFFERENTIAL Eaton/Dana		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Check every 15000 miles, change every 50000 miles</i>		

TRANSMISSION AUTOMATIC Allison		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
<i>Check every 15000 miles, change every 25000 miles</i>		

TRANSMISSION MANUAL Fuller		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 50		
<i>Check every 15000 miles, change every 50000 miles</i>		

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
<i>Check every 7500 miles, change every 60000 miles/ 6 months</i>		



PETERBILT REGIONAL HAUL TRUCKS 337

PACCAR PX-9 (2013-2016)



COOLING SYSTEM

Capacity: 12,4 liter (Engine only)

USE		CLIMATE
On-road use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 750000 miles/ 72 months/ 22000 hours

USE		CLIMATE
Off-road use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 96 months/ 15000 hours

SELECTIVE CATHALYTIC REDUCTION SYSTEM (SCR)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.