

RENAULT (EU) C SERIES EURO 6 C 430

(4X2 / 6X2 / 8X2) EURO 6 (2014-2022)



ENGINE DTi 11
Capacity: 36,5 liter

USE	CLIMATE
Long distance, hilly, 47-70t, PTO use + idle time <25%, fuel =<67 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 35000 km/ 12 months/ 750 hours/ 22500 liter

USE	CLIMATE
Long distance, predominantly flat, 71-80t, PTO use + idle time <25%, fuel =<67 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 60000 km/ 12 months/ 1200 hours/ 22500 liter

USE	CLIMATE
Long distance, hilly, 71-80t, fuel =<100 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 20000 km/ 12 months/ 600 hours/ 22500 liter

USE	CLIMATE
Long distance, >80t, fuel =<100 L/100km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 20000 km/ 12 months/ 600 hours/ 22500 liter

USE	CLIMATE
Distribution, regional, =<32t, fuel =<40 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 60000 km/ 12 months/ 1200 hours/ 22500 liter

USE	CLIMATE
Distribution, regional, 47-70t, fuel =<67 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 35000 km/ 12 months/ 750 hours/ 22500 liter

USE	CLIMATE
Construction site, hilly, 33-46t, fuel =<67 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 35000 km/ 12 months/ 750 hours/ 22500 liter

RENAULT (EU) C SERIES EURO 6 C 430 (4X2 / 6X2 / 8X2) EURO 6 (2014-2022)



USE		CLIMATE
Construction Site, hilly, 47-80t, fuel =<100 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
<i>Change every 20000 km/ 12 months/ 600 hours/ 22500 liter</i>		
USE		CLIMATE
Construction Site, very hilly, >80t, fuel > 100 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
<i>Change every 15000 km/ 12 months/ 600 hours/ 22500 liter</i>		
USE		CLIMATE
Distribution, city, =<32t, fuel =<67 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
<i>Change every 35000 km/ 12 months/ 750 hours/ 22500 liter</i>		
USE		CLIMATE
Distribution, regional, 33-46t, fuel =<50 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
<i>Change every 45000 km/ 12 months/ 900 hours/ 22500 liter</i>		
USE		CLIMATE
Long distance, predominantly flat, PTO use + idle time < 25%, =<46t, max. 90km/h, fuel =< 33 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
<i>Change every 75000 km/ 12 months/ 1250 hours/ 22500 liter</i>		
USE		CLIMATE
Long distance, predominantly flat, 47-70t, PTO use + idle time <25%, fuel =<50 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
<i>Change every 45000 km/ 12 months/ 900 hours/ 22500 liter</i>		
USE		CLIMATE
Construction site, hilly, =<32t, fuel =<50 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
<i>Change every 45000 km/ 12 months/ 900 hours/ 22500 liter</i>		

RENAULT (EU) C SERIES EURO 6 C 430

(4X2 / 6X2 / 8X2) EURO 6 (2014-2022)



DIFFERENTIAL REAR SERVICE CATEGORY (SC) 1 P1361/ P13170/ P1391 (RSH1370F, RSS1344C/D/E), RSS1352A/ RSS1360, RSH1

Capacity: 18 liter (RSH1370F), Capacity: 2 liter (RSH1370F, each hub), Capacity: 11 liter (RSS1344C/D/E), Capacity: 11 liter (RSS1352A), Capacity: 14,5 liter (RSS1360)

USE	CLIMATE
Long distance, hilly, 71-80t, fuel =<100 L/100 km	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		

Change every 60000 km/ 12 months

USE	CLIMATE
Long distance, >80t, fuel =<100 L/100km	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		

Change every 60000 km/ 12 months

USE	CLIMATE
Construction Site, hilly, 47-80t, fuel =<100 L/100 km	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		

Change every 60000 km/ 12 months

USE	CLIMATE
Construction Site, very hilly, >80t, fuel > 100 L/100 km	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		

Change every 600 hours

USE	CLIMATE
Long distance, hilly, 47-70t, PTO use + idle time >25%, fuel >67 L/100 km	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		

Change every 60000 km/ 12 months

USE	CLIMATE
Long distance, predominantly flat, 71-80t, PTO use + idle time >25%, fuel >67 L/100 km	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		

Change every 60000 km/ 12 months

RENAULT (EU) C SERIES EURO 6 C 430 (4X2 / 6X2 / 8X2) EURO 6 (2014-2022)



USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		
Change every 120000 km/ 12 months		

DIFFERENTIAL REAR SERVICE CATEGORY (SC) 2 P1361/ P13170/ P1391 (RSH1370F, RSS1344C/D/E), RSS1352A/ RSS1360, RSH1
Capacity: 18 liter (RSH1370F), Capacity: 2 liter (RSH1370F, each hub), Capacity: 11 liter (RSS1344C/D/E), Capacity: 11 liter (RSS1352A), Capacity: 14,5 liter (RSS1360)

USE		CLIMATE
Long distance, hilly, 71-80t, fuel =<100 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 200000 km/ 36 months		

USE		CLIMATE
Long distance, >80t, fuel =<100 L/100km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 200000 km/ 36 months		

USE		CLIMATE
Construction Site, hilly, 47-80t, fuel =<100 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 200000 km/ 36 months		

USE		CLIMATE
Construction Site, very hilly, >80t, fuel > 100 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 2500 hours		

USE		CLIMATE
Long distance, hilly, 47-70t, PTO use + idle time >25%, fuel >67 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 200000 km/ 36 months		

RENAULT (EU) C SERIES EURO 6 C 430 (4X2 / 6X2 / 8X2) EURO 6 (2014-2022)



USE	CLIMATE
Long distance, predominantly flat, 71-80t, PTO use + idle time >25%, fuel >67 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 36 months

USE	CLIMATE
All other conditions	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 450000 km/ 36 months

RETARDER RET-TH

Capacity: 5,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION MANUAL SERVICE CATEGORY (SC) 2 VT2214B, VT2514B 14/4

Capacity: 13 liter, Capacity: 14,3 liter (+ PTO)

USE	CLIMATE
Long distance, hilly, 71-80t, fuel =<100 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 36 months

USE	CLIMATE
Long distance, >80t, fuel =<100 L/100km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 36 months

USE	CLIMATE
Construction Site, hilly, 47-80t, fuel =<100 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 36 months

USE	CLIMATE
Construction Site, very hilly, >80t, fuel > 100 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 2500 hours

RENAULT (EU) C SERIES EURO 6 C 430 (4X2 / 6X2 / 8X2) EURO 6 (2014-2022)



USE	CLIMATE
Long distance, hilly, 47-70t, PTO use + idle time >25%, fuel >67 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 36 months

USE	CLIMATE
Long distance, predominantly flat, 71-80t, PTO use + idle time >25%, fuel >67 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 36 months

USE	CLIMATE
Long distance, flat or predominantly flat, =<46t	Moderate

PRODUCT RECOMMENDATION 1	
Syngear MT/LD 75W-80	

Change every 450000 km/ 36 months

USE	CLIMATE
Distribution, regional, =<32t	Moderate

PRODUCT RECOMMENDATION 1	
Syngear MT/LD 75W-80	

Change every 450000 km/ 36 months

USE	CLIMATE
All other conditions	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 450000 km/ 36 months

TRANSMISSION MANUAL SERVICE CATEGORY (SC) 4 VT2214B, VT2514B 14/4 Capacity: 13 liter, Capacity: 14,3 liter (+ PTO)

USE	CLIMATE
Long distance, hilly, 71-80t, fuel =<100 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 36 months

RENAULT (EU) C SERIES EURO 6 C 430 (4X2 / 6X2 / 8X2) EURO 6 (2014-2022)



USE		CLIMATE
Long distance, >80t, fuel =<100 L/100km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
Construction Site, hilly, 47-80t, fuel =<100 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
Construction Site, very hilly, >80t, fuel > 100 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 2500 hours</i>		
USE		CLIMATE
Long distance, hilly, 47-70t, PTO use + idle time >25%, fuel >67 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
Long distance, predominantly flat, 71-80t, PTO use + idle time >25%, fuel >67 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 450000 km/ 36 months</i>		

TRANSMISSION SEMI-AUTOMATIC Optidriver ATO 2612D/E/F/G, ATO 3112G, AT 2612F with crawler gears (Vo
Capacity: 16-17,6 liter, Capacity: 16,8-18,4 liter (+ PTO)

RENAULT (EU) C SERIES EURO 6 C 430 (4X2 / 6X2 / 8X2) EURO 6 (2014-2022)



USE		CLIMATE
Long distance, hilly, 71-80t, fuel =<100 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
Long distance, >80t, fuel =<100 L/100km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
Construction Site, hilly, 47-80t, fuel =<100 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
Construction Site, very hilly, >80t, fuel > 100 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 2500 hours</i>		
USE		CLIMATE
Long distance, hilly, 47-70t, PTO use + idle time >25%, fuel >67 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
Long distance, predominantly flat, 71-80t, PTO use + idle time >25%, fuel >67 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 450000 km/ 36 months</i>		

RENAULT (EU) C SERIES EURO 6 C 430

(4X2 / 6X2 / 8X2) EURO 6 (2014-2022)



TRANSMISSION SEMI-AUTOMATIC SERVICE CATEGORY (SC) Optidriver, AT 2412D/E/F/G, AT 2612D/E/F/G, AT 2812G (Volvo I-Shift) 1
Capacity: 16-16,8 liter

USE	CLIMATE
Long distance, hilly, 71-80t, fuel =<100 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 36 months

USE	CLIMATE
Long distance, >80t, fuel =<100 L/100km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 36 months

USE	CLIMATE
Construction Site, hilly, 47-80t, fuel =<100 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 36 months

USE	CLIMATE
Construction Site, very hilly, >80t, fuel > 100 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 2500 hours

USE	CLIMATE
Long distance, hilly, 47-70t, PTO use + idle time >25%, fuel >67 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 36 months

USE	CLIMATE
Long distance, predominantly flat, 71-80t, PTO use + idle time >25%, fuel >67 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 36 months

RENAULT (EU) C SERIES EURO 6 C 430 (4X2 / 6X2 / 8X2) EURO 6 (2014-2022)



USE		CLIMATE
Long distance, flat or predominantly flat, =<46t		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
Change every 450000 km/ 36 months		
USE		CLIMATE
Distribution, regional, =<32t		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
Change every 450000 km/ 36 months		
USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 450000 km/ 36 months		
TRANSMISSION SEMI-AUTOMATIC SERVICE CATEGORY (SC) Optidriver, AT 2412D/E/F/G, AT 2612D/E/F/G, AT 2812G (Volvo I-Shift) 1 Capacity: 16-16,8 liter		
USE		CLIMATE
Long distance, hilly, 71-80t, fuel =<100 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 200000 km/ 36 months		
USE		CLIMATE
Long distance, >80t, fuel =<100 L/100km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 200000 km/ 36 months		
USE		CLIMATE
Construction Site, hilly, 47-80t, fuel =<100 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 200000 km/ 36 months		
USE		CLIMATE
Construction Site, very hilly, >80t, fuel > 100 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 2500 hours		

RENAULT (EU) C SERIES EURO 6 C 430 (4X2 / 6X2 / 8X2) EURO 6 (2014-2022)



USE	CLIMATE
Long distance, hilly, 47-70t, PTO use + idle time >25%, fuel >67 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 200000 km/ 36 months

USE	CLIMATE
Long distance, predominantly flat, 71-80t, PTO use + idle time >25%, fuel >67 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 200000 km/ 36 months

USE	CLIMATE
All other conditions	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 450000 km/ 36 months

HYDRAULIC CAB TILT SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Perlus H 15		

HYDRAULIC CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

RENAULT (EU) C SERIES EURO 6 C 430 (4X2 / 6X2 / 8X2) EURO 6 (2014-2022)

**POWER STEERING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

COOLING SYSTEM

Capacity: 33,5 liter, Capacity: 46,5 liter (+ retarder)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.