

RENAULT (EU) D SERIES EURO 6 D 210 (4X2) EURO 6 (2014 AND AFTER)



ENGINE DTi 5
Capacity: 13,5 liter

USE	CLIMATE
Long distance, predominantly flat, PTO use + idle time < 25%, =<8t, max. 90km/h, fuel =< 20L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Change every 50000 km/ 24 months

USE	CLIMATE
Long distance, predominantly flat, PTO use + idle time < 25%, 9-16t, fuel =<24 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Change every 45000 km/ 24 months

USE	CLIMATE
Long distance, hilly, PTO use + idle time < 25%, 9-16t, fuel =<30 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Change every 40000 km/ 24 months/ 1200 hours/ 12000 liter

USE	CLIMATE
Long distance, hilly, PTO use + idle time < 25%, 8t, fuel =<24 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Change every 45000 km/ 24 months

USE	CLIMATE
Long distance, predominantly flat, >16-36t, PTO use + idle time <25%, fuel =<30 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Change every 40000 km/ 24 months/ 1200 hours/ 12000 liter

USE	CLIMATE
Long distance, hilly, >16-36t, PTO use + idle time <25%, fuel =<35 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Change every 25000 km/ 24 months/ 1000 hours/ 12000 liter

RENAULT (EU) D SERIES EURO 6 D 210 (4X2) EURO 6 (2014 AND AFTER)



USE		CLIMATE
Distribution, regional, >16-36t, fuel =<30 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
<i>Change every 40000 km/ 24 months/ 1200 hours/ 12000 liter</i>		
USE		CLIMATE
Distribution, city, >16-36t, fuel =<35 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
<i>Change every 25000 km/ 24 months/ 1000 hours/ 12000 liter</i>		
USE		CLIMATE
Construction site, hilly or very hilly, >16-36t, fuel =<45 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
<i>Change every 25000 km/ 24 months/ 1000 hours/ 12000 liter</i>		
USE		CLIMATE
Distribution, regional, =<16t, fuel =<24 L/100km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
<i>Change every 45000 km/ 24 months</i>		
USE		CLIMATE
Distribution, city, =<8t, fuel =<24 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
<i>Change every 45000 km/ 24 months</i>		
USE		CLIMATE
Distribution, city, 9-16t, fuel =<30 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
<i>Change every 40000 km/ 24 months/ 1200 hours/ 12000 liter</i>		
USE		CLIMATE
Construction site, hilly, =<8t, fuel =<30 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
<i>Change every 40000 km/ 24 months/ 1200 hours/ 12000 liter</i>		

RENAULT (EU) D SERIES EURO 6 D 210 (4X2) EURO 6 (2014 AND AFTER)



USE		CLIMATE
Construction site, hilly, 9-16t, fuel =<35 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
Change every 25000 km/ 24 months/ 1000 hours/ 12000 liter		

DIFFERENTIAL REAR P 08120 (RSS0819A, MS08125) Capacity: 7 liter		
USE		CLIMATE
Normal service category 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 450000 km/ 36 months		

USE		CLIMATE
Normal service category 1		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		
Change every 120000 km/ 12 months		

USE		CLIMATE
Very severe service category 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 200000 km/ 36 months		

USE		CLIMATE
Very severe service category 1		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		
Change every 60000 km/ 12 months		



RENAULT (EU) D SERIES EURO 6 D 210 (4X2) EURO 6 (2014 AND AFTER)


DIFFERENTIAL REAR P 11140 (RSS1125A)

Capacity: 10,5-12,5 liter

USE		CLIMATE
Normal service category 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 450000 km/ 36 months

USE		CLIMATE
Normal service category 1		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		

Change every 120000 km/ 12 months

USE		CLIMATE
Very severe service category 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 200000 km/ 36 months

USE		CLIMATE
Very severe service category 1		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		

Change every 60000 km/ 12 months

RENAULT (EU) D SERIES EURO 6 D 210 (4X2) EURO 6 (2014 AND AFTER)


DIFFERENTIAL REAR P 11150 (RSS1132A)

Capacity: 15 liter

USE		CLIMATE
Normal service category 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 450000 km/ 36 months

USE		CLIMATE
Normal service category 1		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		

Change every 120000 km/ 12 months

USE		CLIMATE
Very severe service category 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 200000 km/ 36 months

USE		CLIMATE
Very severe service category 1		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		

Change every 60000 km/ 12 months

RENAULT (EU) D SERIES EURO 6 D 210 (4X2) EURO 6 (2014 AND AFTER)


DIFFERENTIAL REAR HUB REDUCTIONS P 1191 (RSH1140C)

Capacity: 17,3 liter, Capacity: 0,5 liter (each hub)

USE		CLIMATE
Normal service category 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 450000 km/ 36 months

USE		CLIMATE
Normal service category 1		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		

Change every 120000 km/ 12 months

USE		CLIMATE
Very severe service category 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 200000 km/ 36 months

USE		CLIMATE
Very severe service category 1		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		

Change every 60000 km/ 12 months

DIFFERENTIAL REAR HUB REDUCTIONS SERVICE CATEGO P 1191/ P 1391 (RSH1140C, RSH1340)

Capacity: 17,3 liter, Capacity: 0,5 liter (each hub)

USE		CLIMATE
Long distance, predominantly flat, PTO use + idle time < 25%, =<8t, max. 90km/h, fuel =< 20L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 240000 km/ 24 months

USE		CLIMATE
Long distance, predominantly flat, PTO use + idle time < 25%, 9-16t, fuel =<24 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 240000 km/ 24 months

RENAULT (EU) D SERIES EURO 6 D 210 (4X2) EURO 6 (2014 AND AFTER)



USE		CLIMATE
Long distance, hilly, PTO use + idle time < 25%, 9-16t, fuel =<30 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Change every 160000 km/ 24 months</i>		
USE		CLIMATE
Long distance, hilly, PTO use + idle time < 25%, 8t, fuel =<24 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Change every 240000 km/ 24 months</i>		
USE		CLIMATE
Long distance, predominantly flat, >16-36t, PTO use + idle time <25%, fuel =<30 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Change every 160000 km/ 24 months</i>		
USE		CLIMATE
Long distance, hilly, >16-36t, PTO use + idle time <25%, fuel =<35 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Change every 120000 km/ 24 months</i>		
USE		CLIMATE
Distribution, regional, >16-36t, fuel =<30 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Change every 160000 km/ 24 months</i>		
USE		CLIMATE
Distribution, city, >16-36t, fuel =<35 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Change every 120000 km/ 24 months</i>		
USE		CLIMATE
Construction site, hilly or very hilly, >16-36t, fuel =<45 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Change every 60000 km/ 12 months</i>		

RENAULT (EU) D SERIES EURO 6 D 210 (4X2) EURO 6 (2014 AND AFTER)



USE		CLIMATE
Distribution, regional, =<16t, fuel =<24 L/100km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 240000 km/ 24 months

USE		CLIMATE
Distribution, city, =<8t, fuel =<24 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 240000 km/ 24 months

USE		CLIMATE
Distribution, city, 9-16t, fuel =<30 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 160000 km/ 24 months

USE		CLIMATE
Construction site, hilly, =<8t, fuel =<30 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 160000 km/ 24 months

USE		CLIMATE
Construction site, hilly, 9-16t, fuel =<35 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 120000 km/ 24 months

TRANSMISSION AUTOMATIC Allison AL205 5/1 Capacity: 10 liter, Capacity: 10,8 liter (+ PTO)

USE		CLIMATE
Distribution, city, >16-36t, fuel =<35 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 20000 km/ 6 months/ 500 hours

USE		CLIMATE
Construction site, hilly or very hilly, >16-36t, fuel =<45 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 20000 km/ 6 months/ 500 hours

RENAULT (EU) D SERIES EURO 6 D 210 (4X2) EURO 6 (2014 AND AFTER)



USE		CLIMATE
Long distance, hilly, >16-36t, PTO use + idle time <25%, fuel =<35 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
<i>Change every 20000 km/ 6 months/ 500 hours</i>		
USE		CLIMATE
with retarder		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
<i>Change every 20000 km/ 6 months/ 500 hours</i>		
USE		CLIMATE
Construction site, hilly, 9-16t, fuel =<35 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
<i>Change every 20000 km/ 6 months/ 500 hours</i>		
USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
<i>Change every 80000 km/ 24 months/ 2000 hours</i>		

TRANSMISSION MANUAL ZF 6S-1000 TO 6/1
Capacity: 10,2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION MANUAL ZF 6S-800 TO 6/1
Capacity: 10,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION SEMI-AUTOMATIC ZF 6AS-1000 (Optitronic) 6/1
Capacity: 10,2 liter, Capacity: 10,7 liter (+ PTO)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION SEMI-AUTOMATIC ZF 6AS-800 (Optitronic) 6/1
Capacity: 10,9 liter, Capacity: 10,4 liter (+ PTO)

We are unable to give a standard recommendation for this component. Please contact our service department.



RENAULT (EU) D SERIES EURO 6 D 210 (4X2) EURO 6 (2014 AND AFTER)



HYDRAULIC CAB TILT SYSTEM

Capacity: 0,7 liter (2 doors), Capacity: 1,5 liter (4 doors)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

HYDRAULIC GEARBOX ACTUATION SYSTEM I-SHIFT SERIES ATO8006 (6AS 800 TO), ATO1056 (6AS 1000TO)

Capacity: 1,15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

HYDRAULIC CLUTCH SYSTEM

Capacity: 0,5 liter

USE		CLIMATE
All conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

POWER STEERING

Capacity: 4 liter

USE		CLIMATE
All conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

COOLING SYSTEM

Capacity: 27,5 liter, Capacity: 32,8 liter (+ Allison automatic gearbox)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.