RENAULT (EU) M MIDLINER M 120 MIDLINER (1990-1996)



ENGINE Perkins Phaser 125 Capacity: 9,5 liter, Filter capacity: 1 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	
Change every 10000 km/ 12 months		

Change every 10000 km/ 12 months

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth 10W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Change every 10000 km/ 12 months

DIFFERENTIAL REAR P 669 Capacity: 5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	SP Gear 1071

Check every 10000 km, change every 60000 km

DIFFERENTIAL REAR P 769 Capacity: 8,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	SP Gear 1071

Check every 10000 km, change every 60000 km

TRANSMISSION MANUAL ZF S5 Capacity: 3,5 liter	35 5/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	Multifleet SCD 30	SP Gear 5015
Check every 10000 km, change eve	ery 60000 km	

RENAULT (EU) M MIDLINER M 120 MIDLINER (1990-1996)



HYDRAULIC CAB TILT SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 10000 km, change every 12 r	months	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
PRODUCT RECOMMENDATION 1 Perlus H 15		
	nonths	

HYDRAULIC BRAKE SYSTEM Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 12 months	'

HYDRAULIC CLUTCH SYSTEM Capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 10000 km, change every	·

POWER STEERING Capacity: 3,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 10000 km	'

RENAULT (EU) M MIDLINER M 120 MIDLINER (1990-1996)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 10000 km		

GREASE POINTS/NIPPLES WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	
Charles a come COOOO less		<u> </u>

Check every 60000 km

COOLING SYSTEM Capacity: 11,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 24 months	'	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.