RENAULT (EU) MAGNUM DXI MAGNUM 520 DXI EURO 5 (2009-2014)



ENGINE DXi 13 Capacity: 33 liter		
USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
Change every 100000 km/ 12 months		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth 5W-30	Dieselfleet MSP 10W-30

Change	everv	80000	km/	12	months
Oriungo	CVCIY	00000	1 (1 1 1/	1 4	1110111111

DIFFERENTIAL REAR P 13170 (R	SS1344C)	
Capacity: 17 liter		
use Severe (preferred)		climate Moderate
		Inouerate
PRODUCT RECOMMENDATION 1 SP Gear 1011	PRODUCT RECOMMENDATION 2 Syngear TDL 75W-90	
Change every 240000 km/ 24 month	ns	
USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 240000 km/24 month	hs	
USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 400000 km/ 36 month	hs	•
USE		CLIMATE
Severe (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 120000 km/ 24 month	hs .	

RENAULT (EU) MAGNUM DXI MAGNUM 520 DXI EURO 5 (2009-2014)



TRANSMISSION SEMI-AUTOMATIC Optidriver+ AT 2612TD (Volvo I-Shift) 12/3 Capacity: 14,5 liter			
USE		CLIMATE	
Normal (alternative)		Moderate	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 40			
Change every 120000 km/ 24 months			
USE		CLIMATE	
Normal (preferred)		Moderate	
PRODUCT RECOMMENDATION 1			
Syngear MT/LD 75W-80			
Change every 400000 km/36 months			

POWER STEERING Capacity: 4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		

COOLING SYSTEM Capacity: 44 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 16	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.