

# SCANIA COACHES OMNICITY CN94UA

## 6X2/2 EURO 2 (ETHANOL) (1998-2001)

**ENGINE** DSI9 E01 Euro 2 (Ethanol)

Capacity: 31 liter, Capacity: 38 liter (Dry fill), Filter capacity: 2 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Armado Synth 10W-40**

## PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

## PRODUCT RECOMMENDATION 3

**Armado Synth 5W-30***Change every 10000 km/ 12 months*

USE	CLIMATE
Normal	Cold

## PRODUCT RECOMMENDATION 1

**Dieselfleet MSP 10W-30***Change every 10000 km/ 12 months***DIFFERENTIAL REAR** ZF AV-132

Capacity: 21 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Unigear HS GL-3/GL-5 80W-90***Check every 20000 km, change every 40000 km***TRANSMISSION AUTOMATIC** ZF 4HP500 4/1

Capacity: 15 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**HYDRAULIC CONTROL SYSTEM ARTICULATED BUS**

Capacity: 2,8 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**ATF Dexron II-D***Check every 80000 km*

# SCANIA COACHES OMNICITY CN94UA 6X2/2 EURO 2 (ETHANOL) (1998-2001)



## HYDRAULIC SYSTEM VENTILATOR

Capacity: 8 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

Check every 20000 km

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Armado Synth 5W-30</b>		

Check every 20000 km

## HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

Check every 20000 km

## POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>ATF Dexron II-D</b>	<b>ATF-A</b>	

Check every 20000 km

## CENTRAL LUBRICATION SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

# SCANIA COACHES OMNICITY CN94UA

## 6X2/2 EURO 2 (ETHANOL) (1998-2001)



### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

Check every 20000 km

### WHEEL BEARINGS REAR OIL LUBRICATED ZF AV-132

Capacity: 0,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Unigear HS GL-3/GL-5 80W-90</b>		

Check every 20000 km, change every 40000 km

### COOLING SYSTEM

Capacity: 40 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

Check every 20000 km, change every 80000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.