SCANIA COACHES OMNILINK CL94UB 4X2 EURO 3 DC9 01 (1999-2006)



ENGINE DC9 01 Euro 3 Capacity: 31 liter, Capacity: 38 liter (Dry fill), Filter capacity: 2 liter			
use Normal		CLIMATE	
		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Armado Synth 10W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30	
USE		CLIMATE	
Normal		Cold	
PRODUCT RECOMMENDATION 1			
Dieselfleet MSP 10W-30			

DIFFERENTIAL REAR R 641, R 642, R 6	653	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

TRANSMISSION AUTOMATIC ZF 4HP502C 4/1

Capacity: 15 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION AUTOMATIC ZF 4HP592C 4/1

Capacity: 15 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION AUTOMATIC ZF 5HP502C 5/1

Capacity: 15 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

SCANIA COACHES OMNILINK CL94UB 4X2 EURO 3 DC9 01 (1999-2006)



TRANSMISSION AUTOMATIC ZF 5HP592C 5/1

Capacity: 15 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC SYSTEM VENTILATOR Capacity: 8 liter	₹	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Armado Synth 5W-30		

Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
HYDRAULIC CLUTCH SYSTEM		

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-A	

CENTRAL LUBRICATION SYSTEM	Л	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SCANIA COACHES OMNILINK CL94UB 4X2 EURO 3 DC9 01 (1999-2006)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 40 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.