

SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)

**ENGINE** DC9 22 320 Euro 5

Capacity: 33 liter (-> 10/2007), Capacity: 31 liter (10/2007 ->), Filter capacity: 2 liter (-> 10/2007), Filter capacity: 1 liter (10/2007 ->)

USE	CLIMATE
Distribution (preferred)	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth 10W-40*Change every 45000 km/ 12 months*

USE	CLIMATE
Construction Site (preferred)	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth 10W-40*Change every 20000 km/ 12 months*

USE	CLIMATE
Heavy duty long distance (preferred)	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth 10W-40*Change every 30000 km/ 12 months*

USE	CLIMATE
Heavy duty long distance (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 2

Armado Synth MSP 5W-40

PRODUCT RECOMMENDATION 3

Dieselfleet MSP 15W-40*Change every 15000 km/ 12 months*

USE	CLIMATE
Heavy duty long distance (alternative)	Cold

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 5W-30

PRODUCT RECOMMENDATION 2

Dieselfleet LSP Ultra 10W-30

PRODUCT RECOMMENDATION 3

Dieselfleet MSP 10W-30*Change every 15000 km/ 12 months*

USE	CLIMATE
Long distance (preferred)	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth 10W-40*Change every 60000 km/ 12 months*

USE	CLIMATE
Light Duty, long distance (preferred)	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth 10W-40*Change every 90000 km/ 12 months*

SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)



USE		CLIMATE
Light duty long distance (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40	Dieselfleet MSP 15W-40
<i>Change every 45000 km/ 12 months</i>		
USE		CLIMATE
Light duty long distance (alternative)		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30
<i>Change every 45000 km/ 12 months</i>		
USE		CLIMATE
Long distance (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40	Dieselfleet MSP 15W-40
<i>Change every 30000 km/ 12 months</i>		
USE		CLIMATE
Long distance (alternative)		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30
<i>Change every 30000 km/ 12 months</i>		
USE		CLIMATE
Distribution (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40	Dieselfleet MSP 15W-40
<i>Change every 20000 km/ 12 months</i>		
USE		CLIMATE
Distribution (alternative)		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30
<i>Change every 20000 km/ 12 months</i>		
USE		CLIMATE
Construction Site (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40	Dieselfleet MSP 15W-40
<i>Change every 10000 km/ 12 months</i>		

SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)



USE		CLIMATE
Construction Site (alternative)		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30
Change every 10000 km/ 12 months		

DIFFERENTIAL FRONT HUB REDUCTIONS RP 731 (4x4) (6x6)
Capacity: 13,5 liter (Axle gear case), Capacity: 0,8 liter (each hub)

USE		CLIMATE
Heavy duty long distance		Moderate
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 120000 km/ 24 months		

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 80000 km/ 24 months		

USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 120000 km/ 24 months		

USE		CLIMATE
Long distance (alternative)		Moderate
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 240000 km/ 24 months		



SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)


DIFFERENTIAL FRONT HUB REDUCTIONS WITHOUT FILTER RP 731 (4x4) (6x6)

Capacity: 13,5 liter, Capacity: 0,8 liter (each hub)

USE	CLIMATE
Heavy duty long distance	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 60000 km/ 12 months*

USE	CLIMATE
Long distance	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 120000 km/ 12 months*

USE	CLIMATE
Construction Site	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 40000 km/ 12 months*

USE	CLIMATE
Distribution	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 60000 km/ 12 months*

SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)


DIFFERENTIAL REAR HUB REDUCTIONS RP 835

Capacity: 12 liter (Axle gear case), Capacity: 2 liter (each hub)

USE	CLIMATE
Heavy duty long distance	Moderate

PRODUCT RECOMMENDATION 1 Unigear LS GL-3/GL-5 85W-140		
---	--	--

Change every 120000 km/ 24 months

USE	CLIMATE
Construction Site	Moderate

PRODUCT RECOMMENDATION 1 Unigear LS GL-3/GL-5 85W-140		
---	--	--

Change every 80000 km/ 24 months

USE	CLIMATE
Distribution	Moderate

PRODUCT RECOMMENDATION 1 Unigear LS GL-3/GL-5 85W-140		
---	--	--

Change every 120000 km/ 24 months

USE	CLIMATE
Long distance (alternative)	Moderate

PRODUCT RECOMMENDATION 1 Unigear LS GL-3/GL-5 85W-140		
---	--	--

Change every 240000 km/ 24 months

SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)


DIFFERENTIAL REAR HUB REDUCTIONS WITHOUT FILTER RP 835

Capacity: 12 liter (Axle gear case), Capacity: 2 liter (each hub)

USE	CLIMATE
Heavy duty long distance	Moderate

PRODUCT RECOMMENDATION 1 Unigear LS GL-3/GL-5 85W-140		
---	--	--

Change every 60000 km/ 12 months

USE	CLIMATE
Long distance	Moderate

PRODUCT RECOMMENDATION 1 Unigear LS GL-3/GL-5 85W-140		
---	--	--

Change every 120000 km/ 12 months

USE	CLIMATE
Construction Site	Moderate

PRODUCT RECOMMENDATION 1 Unigear LS GL-3/GL-5 85W-140		
---	--	--

Change every 40000 km/ 12 months

USE	CLIMATE
Distribution	Moderate

PRODUCT RECOMMENDATION 1 Unigear LS GL-3/GL-5 85W-140		
---	--	--

Change every 60000 km/ 12 months

SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)

**RETARDER** Scania

Capacity: 7,9 liter (Initial fill), Capacity: 7,7 liter (Service fill)

USE		CLIMATE
Heavy duty long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 60000 km/ 36 months

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 120000 km/ 36 months

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 80000 km/ 36 months

USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 60000 km/ 36 months

RETARDER TYPE 2 Scania R3500, R4100, R4100D, 4700D		
USE		CLIMATE
Distribution (preferred)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 120000 km/ 36 months

USE		CLIMATE
Construction Site (preferred)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 80000 km/ 36 months

SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)



USE		CLIMATE
Heavy duty long distance (preferred)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
<i>Change every 120000 km/ 36 months</i>		
USE		CLIMATE
Heavy duty long distance (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet LSP Ultra 10W-30	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
<i>Change every 60000 km/ 36 months</i>		
USE		CLIMATE
Long distance (preferred)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
<i>Change every 360000 km/ 36 months</i>		
USE		CLIMATE
Long distance (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet LSP Ultra 10W-30	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
<i>Change every 240000 km/ 36 months</i>		
USE		CLIMATE
Distribution (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet LSP Ultra 10W-30	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
<i>Change every 60000 km/ 36 months</i>		
USE		CLIMATE
Construction Site (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet LSP Ultra 10W-30	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
<i>Change every 80000 km/ 36 months</i>		



SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)


TRANSFERBOX GTD 800 (4x4)

Capacity: 6,5 liter

USE		CLIMATE
Heavy duty long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear HS 75W-90

Change every 60000 km/ 12 months

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear HS 75W-90

Change every 20000 km/ 12 months

USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear HS 75W-90

Change every 20000 km/ 12 months

TRANSMISSION AUTOMATIC GA 851/852/866/867 (Allison HD) 6/1

Capacity: 50 liter (Overhaul capacity), Capacity: 34 liter (Service fill)

USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Change every 120000 km/ 36 months

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 20000 km/ 6 months

TRANSMISSION MANUAL GR 875 (R) 8/1

Capacity: 15 liter, Capacity: 17 liter (+ oil cooler (air cooled)), Capacity: 16 liter (+ oil cooler (liquid cooled))

USE		CLIMATE
Heavy duty long distance		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km/ 24 months

SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)



USE Heavy duty long distance		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 SP Gear 1011	PRODUCT RECOMMENDATION 2 Syngear TDL 75W-90	PRODUCT RECOMMENDATION 3 Unigear HS GL-3/GL-5 80W-90
<i>Change every 120000 km/ 24 months</i>		
USE Long distance (preferred)		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 SP Gear 1011	PRODUCT RECOMMENDATION 2 Syngear TDL 75W-90	
<i>Change every 360000 km/ 24 months</i>		
USE Construction Site		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1 Unigear LS GL-3/GL-5 85W-140		
<i>Change every 80000 km/ 24 months</i>		
USE Construction Site		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 SP Gear 1011	PRODUCT RECOMMENDATION 2 Syngear TDL 75W-90	PRODUCT RECOMMENDATION 3 Unigear HS GL-3/GL-5 80W-90
<i>Change every 80000 km/ 24 months</i>		
USE Distribution		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1 Unigear LS GL-3/GL-5 85W-140		
<i>Change every 120000 km/ 24 months</i>		
USE Distribution		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 SP Gear 1011	PRODUCT RECOMMENDATION 2 Syngear TDL 75W-90	PRODUCT RECOMMENDATION 3 Unigear HS GL-3/GL-5 80W-90
<i>Change every 120000 km/ 24 months</i>		
USE Long distance (alternative)		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1 Unigear LS GL-3/GL-5 85W-140		
<i>Change every 240000 km/ 24 months</i>		

SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)



USE		CLIMATE
Long distance (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90
Change every 240000 km/ 24 months		

TRANSMISSION MANUAL GR 905 (R) 8/1 Capacity: 16,5 liter

USE		CLIMATE
Heavy duty long distance		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 120000 km/ 24 months		

USE		CLIMATE
Heavy duty long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90
Change every 120000 km/ 24 months		

USE		CLIMATE
Long distance (preferred)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 360000 km/ 24 months		

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 80000 km/ 24 months		

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90
Change every 80000 km/ 24 months		

USE		CLIMATE
Distribution		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 120000 km/ 24 months		

SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)



USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 120000 km/ 24 months

USE		CLIMATE
Long distance (alternative)		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 240000 km/ 24 months

USE		CLIMATE
Long distance (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 240000 km/ 24 months

TRANSMISSION MANUAL GRS 895 (R) 12/2

Capacity: 15 liter, Capacity: 17 liter (+ oil cooler (air cooled)), Capacity: 16 liter (+ oil cooler (liquid cooled))

USE		CLIMATE
Heavy duty long distance		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km/ 24 months

USE		CLIMATE
Heavy duty long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 120000 km/ 24 months

USE		CLIMATE
Long distance (preferred)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 360000 km/ 24 months

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km/ 24 months

SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)



USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 80000 km/ 24 months

USE		CLIMATE
Distribution		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km/ 24 months

USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 120000 km/ 24 months

USE		CLIMATE
Long distance (alternative)		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 240000 km/ 24 months

USE		CLIMATE
Long distance (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 240000 km/ 24 months

TRANSMISSION MANUAL GRSO 905 12/2

USE		CLIMATE
Heavy duty long distance		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km/ 24 months

USE		CLIMATE
Heavy duty long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 120000 km/ 24 months

SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)



USE		CLIMATE
Long distance (preferred)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 360000 km/ 24 months</i>		
USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
<i>Change every 80000 km/ 24 months</i>		
USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90
<i>Change every 80000 km/ 24 months</i>		
USE		CLIMATE
Distribution		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
<i>Change every 120000 km/ 24 months</i>		
USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90
<i>Change every 120000 km/ 24 months</i>		
USE		CLIMATE
Long distance (alternative)		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
<i>Change every 240000 km/ 24 months</i>		
USE		CLIMATE
Long distance (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90
<i>Change every 240000 km/ 24 months</i>		



SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)



HYDRAULIC CAB TILT SYSTEM

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4036	SP Matic 2032	ATF Almirol

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 15		

HYDRAULIC DAMPER Opticruise

Capacity: 0,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

HYDRAULIC SYSTEM VENTILATOR

Capacity: 8 liter, Capacity: 15 liter (Initial fill)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Armado Synth 5W-30		

SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)



HYDRAULIC CLUTCH SYSTEM

Capacity: 0,4 liter

USE		CLIMATE
Heavy duty long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 240000 km/ 24 months

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 480000 km/ 24 months

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 160000 km/ 24 months

USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 240000 km/ 24 months

POWER STEERING

Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-A	

CENTRAL LUBRICATION SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SCANIA G SERIES G-320 EURO 5 + DPF (4X4) (2008 AND AFTER)

**COOLING SYSTEM**

Capacity: 30 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 600000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.