

SCANIA R SERIES R-360 EURO 5 (4X4)

(2008 AND AFTER)



ENGINE DC13 06 Euro 5
Capacity: 40 liter, Filter capacity: 1 liter

USE	CLIMATE
Preferred, extended	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth 10W-40

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth 10W-40

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Armado Synth 5W-30

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 2

Armado Synth LSP 10W-40

PRODUCT RECOMMENDATION 3

Armado Synth 10W-40

USE	CLIMATE
Alternative (acceptable)	Cold

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 5W-30

PRODUCT RECOMMENDATION 2

Armado Synth 5W-30

DIFFERENTIAL FRONT HUB REDUCTIONS RP 731 (4x4) (6x6)

Capacity: 13,5 liter (Axle gear case), Capacity: 0,8 liter (each hub)

USE	CLIMATE
Construction Site	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140

Change every 80000 km

SCANIA R SERIES R-360 EURO 5 (4X4)

(2008 AND AFTER)

**DIFFERENTIAL REAR HUB REDUCTIONS** RP 835

Capacity: 12 liter (Axle gear case), Capacity: 2 liter (each hub)

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

*Change every 80000 km***POWER TAKE OFF**

Capacity: 0,5-2,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

RETARDER Scania

Capacity: 7,9 liter (Initial fill), Capacity: 7,7 liter (Service fill)

USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

*Change every 80000 km***TRANSFERBOX** GTD 800

Capacity: 6,5 liter

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 20000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Change every 20000 km

SCANIA R SERIES R-360 EURO 5 (4X4)

(2008 AND AFTER)



TRANSMISSION AUTOMATIC GA 851/852/866/867 (Allison HD) 6/1
Capacity: 50 liter (Overhaul capacity), Capacity: 34 liter (Service fill)

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Change every 20000 km

TRANSMISSION MANUAL GR 905 (R) 8/1
Capacity: 16,5 liter

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 80000 km

TRANSMISSION MANUAL GRS 895 (R) 12/2
Capacity: 15 liter, Capacity: 17 liter (+ oil cooler (air cooled)), Capacity: 16 liter (+ oil cooler (liquid cooled))

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 80000 km

SCANIA R SERIES R-360 EURO 5 (4X4)

(2008 AND AFTER)


TRANSMISSION MANUAL GRS 905 12/2

Capacity: 16,5 liter

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 80000 km
TRANSMISSION MANUAL GRSO 905 12/2

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 80000 km
HYDRAULIC CAB TILT SYSTEM

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4036	SP Matic 2032	ATF Almirol

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 15		

SCANIA R SERIES R-360 EURO 5 (4X4)

(2008 AND AFTER)

**HYDRAULIC DAMPER** Opticruise

Capacity: 0,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

HYDRAULIC SYSTEM VENTILATOR

Capacity: 8 liter, Capacity: 15 liter (Initial fill)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Armado Synth 5W-30		

HYDRAULIC CLUTCH SYSTEM

Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

*Change every 12 months***POWER STEERING**

Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-A	

CENTRAL LUBRICATION SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SCANIA R SERIES R-360 EURO 5 (4X4) (2008 AND AFTER)

**COOLING SYSTEM**

Capacity: 44 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.