

SEDDON ATKINSON PACER PACER M5

26.275NDD (6X4) (2001-2007)



ENGINE Iveco F4AE0681A*C Tector
Capacity: 10,8 liter, Filter capacity: 1 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

Change every 80000 km/ 12 months

DIFFERENTIAL REAR LEADING Meritor RT52-153
Capacity: 20,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube HS GL-5 80W-140

PRODUCT RECOMMENDATION 2

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 3

Unigear LS GL-3/GL-5 85W-140

Check every 80000 km/ 12 months, change every 160000 km/ 3200 hours

DIFFERENTIAL REAR TRAILING Meritor RT52-153
Capacity: 16,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube HS GL-5 80W-140

PRODUCT RECOMMENDATION 2

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 3

Unigear LS GL-3/GL-5 85W-140

Check every 80000 km/ 12 months, change every 160000 km/ 3200 hours

TRANSMISSION AUTOMATIC Allison MD 3560P 5/1
Capacity: 18 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

Check every 80000 km/ 12 months, change every 120000 km/ 3000 hours/ 36 months

HYDRAULIC CAB TILT SYSTEM

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Perlus H 15

Check every 80000 km/ 12 months

SEDDON ATKINSON PACER PACER M5

26.275NDD (6X4) (2001-2007)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 80000 km/ 12 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 80000 km/ 12 months

WHEEL BEARINGS OIL LUBRICATED Meritor RT52-153

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Check every 80000 km/ 12 months, change every 160000 km/ 3200 hours

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 12 months, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.