

# SEDDON ATKINSON STRATO STRATO R6

## 32.345MDD (8X4) (2001-2007)



**ENGINE** Cummins ISMe 345  
Capacity: 39 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

Change every 60000 km/ 1200 hours/ 6 months

**DIFFERENTIAL REAR LEADING** Meritor RT52-153  
Capacity: 20,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Gearlube HS GL-5 80W-140</b>	<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>

Check every 60000 km/ 6 months/ 1200 hours, change every 160000 km/ 3200 hours

**DIFFERENTIAL REAR TRAILING** Meritor RT52-153  
Capacity: 16,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Gearlube HS GL-5 80W-140</b>	<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>

Check every 60000 km/ 6 months/ 1200 hours, change every 160000 km/ 3200 hours

**TRANSMISSION MANUAL** ZF 16S-221 16/2  
Capacity: 13 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>Syngear MT/LD 75W-80</b>	<b>Syngear TDL 75W-90</b>

Check every 60000 km/ 6 months/ 1200 hours, change every 300000 km/ 24 months

### HYDRAULIC CAB TILT SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus H 15</b>		

Check every 60000 km/ 6 months/ 1200 hours

# SEDDON ATKINSON STRATO STRATO R6

## 32.345MDD (8X4) (2001-2007)



### POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	

Check every 60000 km/ 6 months/ 1200 hours

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

Check every 60000 km/ 6 months/ 1200 hours

### WHEEL BEARINGS OIL LUBRICATED Meritor RT52-153

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Gearlube HS GL-5 80W-140</b>	<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>

Check every 60000 km/ 6 months/ 1200 hours, change every 160000 km/ 3200 hours

### COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Check every 60000 km/ 6 months/ 1200 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.