

VDL (BOVA/BERKHOF) FH FUTURA FHD 10.340, FHD 12.340 (1991 AND AFTER)



ENGINE DAF WS 242 L
Capacity: 29 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	

Change every 20000 km

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Change every 20000 km

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Armado Synth 5W-30	Multifleet SCD 20W-20

Change every 20000 km

DIFFERENTIAL REAR ZF A-131
Capacity: 22 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Check every 20000 km, change every 60000 km

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 20000 km, change every 60000 km

VDL (BOVA/BERKHOF) FH FUTURA FHD 10.340, FHD 12.340 (1991 AND AFTER)

**HUB REDUCTIONS REAR ZF A-131**

Capacity: 0,7 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Check every 20000 km, change every 60000 km

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 20000 km, change every 60000 km

TRANSMISSION MANUAL ZF S6-85 6/1

Capacity: 11 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 40000 km, change every 60000 km

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	SP Gear 5015	Gearlube GL-4 80W

Check every 40000 km, change every 60000 km

TRANSMISSION MANUAL ZF S8-180 8/1

Capacity: 17 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 40000 km, change every 60000 km

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	SP Gear 5015	Gearlube GL-4 80W

Check every 40000 km, change every 60000 km

VDL (BOVA/BERKHOF) FH FUTURA FHD 10.340, FHD 12.340 (1991 AND AFTER)



HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Change every 60000 km		

POWER STEERING ZF 8043

Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D
Change every 60000 km		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	Multi Purpose Grease 3
Check every 20000 km		

COOLING SYSTEM

Capacity: 50 liter, Capacity: 79 liter (+ heater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 80000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.