

# YAMZ 650/651/652 6521 ECE 96-02 (2009 AND AFTER)

**ENGINE**

Capacity: 36,4 liter (Dry fill), Capacity: 34 liter (Service fill)

**USE**

Fuel sulfur level &gt;0.2% (2000ppm)

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Armado Synth LSP Ultra 5W-30****PRODUCT RECOMMENDATION 2****Armado Synth LSP 10W-40****PRODUCT RECOMMENDATION 3****Armado Synth 10W-40***Change every 20000 km/ 400 hours***USE**

Fuel sulfur level &lt;0,2%

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Armado Synth LSP Ultra 5W-30****PRODUCT RECOMMENDATION 2****Armado Synth LSP 10W-40****PRODUCT RECOMMENDATION 3****Armado Synth 10W-40***Change every 40000 km/ 800 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.