

**TRANSMISSION MANUAL 8/1**

Capacity: 10,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Syngear MT/LD 75W-80*Change every 240000 km/ 24 months*

USE	CLIMATE
Normal (alternative)	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear MT/LD 75W-80

PRODUCT RECOMMENDATION 3

Syngear TDL 75W-90*Change every 120000 km/ 12 months*

USE	CLIMATE
Off-road, stationary use (alternative)	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear MT/LD 75W-80

PRODUCT RECOMMENDATION 3

Syngear TDL 75W-90*Change every 20000 km/ 12 months/ 1000 hours*

USE	CLIMATE
Off-road, stationary use	Moderate

PRODUCT RECOMMENDATION 1

Syngear MT/LD 75W-80*Change every 100000 km/ 12 months/ 5000 hours*

USE	CLIMATE
Long distance	Moderate

PRODUCT RECOMMENDATION 1

Syngear MT/LD 75W-80*Change every 360000 km/ 24 months*

USE	CLIMATE
Long distance (alternative)	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear MT/LD 75W-80

PRODUCT RECOMMENDATION 3

Syngear TDL 75W-90*Change every 180000 km/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.