

# BMC PROFESSIONAL / PROFESYONEL PRO 827 4X2/6X2/8X2 EURO 1 (2006-2010)



**MOTOR** Cummins C8.3 (Euro 1)  
Kapacitet: 24 liter

| ANVEND       | KLIMA   |
|--------------|---------|
| Langdistance | Moderat |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           |
|-------------------------------|-------------------------------|
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Skift alle 20000 km/ 3 måneder/ 250 timer

| ANVEND              | KLIMA   |
|---------------------|---------|
| Alle øvrige forhold | Moderat |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           |
|-------------------------------|-------------------------------|
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Skift alle 10000 km/ 3 måneder/ 250 timer

**DIFFERENTIALE BAG** Meritor MS-18  
Kapacitet: 21 liter

| ANVEND       | KLIMA   |
|--------------|---------|
| Langdistance | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Skift alle 60000 km/ 12 måneder/ 1000 timer

| ANVEND              | KLIMA   |
|---------------------|---------|
| Alle øvrige forhold | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Skift alle 40000 km/ 6 måneder/ 500 timer

**GEAR MANUEL** ZF 16S-109 DT 16/2  
Kapacitet: 9 liter

| ANVEND       | KLIMA   |
|--------------|---------|
| Langdistance | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-4 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Skift alle 60000 km/ 12 måneder/ 1000 timer

| ANVEND              | KLIMA   |
|---------------------|---------|
| Alle øvrige forhold | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-4 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Skift alle 40000 km/ 6 måneder/ 500 timer

# BMC PROFESSIONAL / PROFESYONEL PRO 827 4X2/6X2/8X2 EURO 1 (2006-2010)



## HYDRAULISK TIPPESTYSTEM FOR KABINEN

| ANVEND              |  | KLIMA   |
|---------------------|--|---------|
| Normal              |  | Moderat |
| PRODUKTANBEFALING 1 |  |         |
| <b>Perlus H 15</b>  |  |         |

## HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0,3 liter

| ANVEND                           |                           | KLIMA   |
|----------------------------------|---------------------------|---------|
| Langdistance                     |                           | Moderat |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |         |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |         |

Kontroller alle 20000 km/ 3 måneder/ 250 timer, skift alle 60000 km/ 12 måneder/ 1000 timer

| ANVEND                           |                           | KLIMA   |
|----------------------------------|---------------------------|---------|
| Alle øvrige forhold              |                           | Moderat |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |         |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |         |

Kontroller alle 10000 km/ 3 måneder/ 250 timer, skift alle 40000 km/ 6 måneder/ 500 timer

## SERVOSTYRING

Kapacitet: 2,9 liter

| ANVEND                 |  | KLIMA   |
|------------------------|--|---------|
| Langdistance           |  | Moderat |
| PRODUKTANBEFALING 1    |  |         |
| <b>ATF Dexron II-D</b> |  |         |

Kontroller alle 20000 km/ 3 måneder/ 250 timer, skift alle 60000 km/ 12 måneder/ 1000 timer

| ANVEND                 |  | KLIMA   |
|------------------------|--|---------|
| Alle øvrige forhold    |  | Moderat |
| PRODUKTANBEFALING 1    |  |         |
| <b>ATF Dexron II-D</b> |  |         |

Kontroller alle 10000 km/ 3 måneder/ 250 timer, skift alle 40000 km/ 6 måneder/ 500 timer

## CENTRALT SMØRINGSSYSTEM

| ANVEND                  |  | KLIMA   |
|-------------------------|--|---------|
| Normal                  |  | Moderat |
| PRODUKTANBEFALING 1     |  |         |
| <b>Gear Grease EP 0</b> |  |         |

# BMC PROFESSIONAL / PROFESYONEL

## PRO 827 4X2/6X2/8X2 EURO 1 (2006-2010)



### SMØREPUNKTER/NIPLER GENEREELT

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

### KØLESYSTEM

Kapacitet: 32,5 liter

| ANVEND                |                      | KLIMA   |
|-----------------------|----------------------|---------|
| Normal                |                      | Moderat |
| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2  |         |
| <b>Coolant SP 15+</b> | <b>Coolant SP 12</b> |         |

Skift alle 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.