

# DANA SPICER AXLES STYREAKSLER. E-SERIE E-1201W



## BINDESTANGSENDE

|                |         |
|----------------|---------|
| ANVEND         | KLIMA   |
| Linjetransport | Moderat |

|                      |                                 |                              |
|----------------------|---------------------------------|------------------------------|
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Skift alle 40000 km/ 6 måneder

|                |         |
|----------------|---------|
| ANVEND         | KLIMA   |
| Erhvervsmæssig | Moderat |

|                      |                                 |                              |
|----------------------|---------------------------------|------------------------------|
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Skift alle 50 timer

## HJULLEJER (JUSTERBAR)

|                         |         |
|-------------------------|---------|
| ANVEND                  | KLIMA   |
| Linjetransport, oliebad | Moderat |

|                                |                     |                           |
|--------------------------------|---------------------|---------------------------|
| PRODUKTANBEFALING 1            | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3       |
| <b>Gearlube Racing 75W-140</b> | <b>SP Gear 1011</b> | <b>Syngear TDL 75W-90</b> |

Skift alle 200000 km/ 12 måneder

|                         |         |
|-------------------------|---------|
| ANVEND                  | KLIMA   |
| Linjetransport, oliebad | Arktisk |

|                     |  |  |
|---------------------|--|--|
| PRODUKTANBEFALING 1 |  |  |
| <b>SP Gear 5015</b> |  |  |

Skift alle 200000 km/ 12 måneder

|                            |         |
|----------------------------|---------|
| ANVEND                     | KLIMA   |
| Linjetransport, smørepakke | Moderat |

|                      |                                 |                              |
|----------------------|---------------------------------|------------------------------|
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Skift alle 200000 km/ 12 måneder

|                   |         |
|-------------------|---------|
| ANVEND            | KLIMA   |
| Varevogn, oliebad | Moderat |

|                                |                     |                           |
|--------------------------------|---------------------|---------------------------|
| PRODUKTANBEFALING 1            | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3       |
| <b>Gearlube Racing 75W-140</b> | <b>SP Gear 1011</b> | <b>Syngear TDL 75W-90</b> |

Skift alle 100000 km/ 6 måneder

|                   |         |
|-------------------|---------|
| ANVEND            | KLIMA   |
| Varevogn, oliebad | Arktisk |

|                     |  |  |
|---------------------|--|--|
| PRODUKTANBEFALING 1 |  |  |
| <b>SP Gear 5015</b> |  |  |

Skift alle 100000 km/ 6 måneder

# DANA SPICER AXLES STYREAKSLER. E-SERIE E-1201W



| ANVEND                          |                                 | KLIMA                        |
|---------------------------------|---------------------------------|------------------------------|
| Varevogn, smørepakke            |                                 | Moderat                      |
| PRODUKTANBEFALING 1             | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b>            | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |
| Skift alle 100000 km/ 6 måneder |                                 |                              |

| HJULLEJER (LMS-SYSTEM)           |                           |         |
|----------------------------------|---------------------------|---------|
| ANVEND                           |                           | KLIMA   |
| Linjetransport                   |                           | Moderat |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |         |
| <b>SP Gear 1011</b>              | <b>Syngear TDL 75W-90</b> |         |
| Skift alle 800000 km/ 60 måneder |                           |         |

| ANVEND                           |                           | KLIMA   |
|----------------------------------|---------------------------|---------|
| Erhvervsmæssig                   |                           | Moderat |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |         |
| <b>SP Gear 1011</b>              | <b>Syngear TDL 75W-90</b> |         |
| Skift alle 200000 km/ 24 måneder |                           |         |

| STYREBOLTSSAMLING              |                                 |                              |
|--------------------------------|---------------------------------|------------------------------|
| ANVEND                         |                                 | KLIMA                        |
| Linjetransport                 |                                 | Moderat                      |
| PRODUKTANBEFALING 1            | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b>           | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |
| Skift alle 40000 km/ 6 måneder |                                 |                              |
| ANVEND                         |                                 | KLIMA                        |
| Erhvervsmæssig                 |                                 | Moderat                      |
| PRODUKTANBEFALING 1            | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b>           | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |
| Skift alle 50 timer            |                                 |                              |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.