EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED FROF-16210B



TRANSMISSION Eaton-Fuller 16210 10		
Capacity: 11 liter		
Standard, line haul	1	Moderate
PRODUCT RECOMMENDATION 1 Multifleet SCD 50	PRODUCT RECOMMENDATION 2 Multifleet SCD 40	PRODUCT RECOMMENDATION 3 Gearlube GL-4 80W-90
	Multineet SCD 40	Geanube GL-4 80W-90
Change every 100000 km		
		CLIMATE
Standard, line haul	1	Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 100000 km		
USE		CLIMATE
Standard, vocational/bus		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90
Change every 100000 km/ 12 months		
USE		CLIMATE
Standard, vocational/bus		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 100000 km/ 12 months		
USE		CLIMATE
Standard, stationary		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90
Change every 500 hours/ 12 months		
USE		CLIMATE
Standard, stationary		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 500 hours/ 12 months		
USE		CLIMATE
Standard, initial service, stationary		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90

EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED FROF-16210B



use Standard, initial service, stationary		climate Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 2 months/ 40 hours		
USE		CLIMATE
Standard, initial service, on highway	use	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90
Change every 8000 km		
USE		CLIMATE
Standard, initial service, on highway	use	Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 8000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.