

EATON FULLER TRANSMISSIONER 5 -> 7 HASTIGHEDER, TUNG BELASTNING T- 11605A



GEAR Eaton-Fuller 11605 5/1
Kapacitet: 10 liter

ANVEND

Terrænanvendelse, startservice

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

Skift alle 30 timer

ANVEND

Terrænanvendelse, startservice

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 50

PRODUKTANBEFALING 2

Multifleet SCD 40

PRODUKTANBEFALING 3

HDX 50

Skift alle 30 timer

ANVEND

Terrænanvendelse, startservice

KLIMA

Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 30

PRODUKTANBEFALING 2

HDX 30

Skift alle 30 timer

ANVEND

Motorvejsanvendelse, startservice

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

Skift alle 8000 km

ANVEND

Motorvejsanvendelse, startservice

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 50

PRODUKTANBEFALING 2

Multifleet SCD 40

PRODUKTANBEFALING 3

HDX 50

Skift alle 8000 km

ANVEND

Motorvejsanvendelse, startservice

KLIMA

Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 30

PRODUKTANBEFALING 2

HDX 30

Skift alle 8000 km

ANVEND

Terrænanvendelse, svær

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

Kontroller alle 40 timer, skift alle 500 timer

EATON FULLER TRANSMISSIONER 5 -> 7 HASTIGHEDER, TUNG BELASTNING T- 11605A



ANVEND Terrænanvendelse, svær		KLIMA Moderat
PRODUKTANBEFALING 1 Multifleet SCD 50	PRODUKTANBEFALING 2 Multifleet SCD 40	PRODUKTANBEFALING 3 HDX 50
Kontroller alle 40 timer, skift alle 500 timer		
ANVEND Terrænanvendelse, svær		KLIMA Arktisk
PRODUKTANBEFALING 1 Multifleet SCD 30	PRODUKTANBEFALING 2 HDX 30	
Kontroller alle 40 timer, skift alle 500 timer		
ANVEND Terrænanvendelse		KLIMA Middelhavsagtigt
PRODUKTANBEFALING 1 Gearlube GL-4 80W-90		
Kontroller alle 40 timer, skift alle 1000 timer		
ANVEND Terrænanvendelse		KLIMA Moderat
PRODUKTANBEFALING 1 Multifleet SCD 50	PRODUKTANBEFALING 2 Multifleet SCD 40	PRODUKTANBEFALING 3 HDX 50
Kontroller alle 40 timer, skift alle 1000 timer		
ANVEND Terrænanvendelse		KLIMA Arktisk
PRODUKTANBEFALING 1 Multifleet SCD 30	PRODUKTANBEFALING 2 HDX 30	
Kontroller alle 40 timer, skift alle 1000 timer		
ANVEND Motorvejsanvendelse		KLIMA Middelhavsagtigt
PRODUKTANBEFALING 1 Gearlube GL-4 80W-90		
Kontroller alle 16000 km, skift alle 80000 km		
ANVEND Motorvejsanvendelse		KLIMA Moderat
PRODUKTANBEFALING 1 Multifleet SCD 50	PRODUKTANBEFALING 2 Multifleet SCD 40	PRODUKTANBEFALING 3 HDX 50
Kontroller alle 16000 km, skift alle 80000 km		

EATON FULLER TRANSMISSIONER 5 -> 7 HASTIGHEDER, TUNG BELASTNING T- 11605A



ANVEND

Motorvejsanvendelse

KLIMA

Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 30

PRODUKTANBEFALING 2

HDX 30*Kontroller alle 16000 km, skift alle 80000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.