

EATON FULLER TRANSMISSIONER 8 HASTIGHEDER, TUNG BELASTNING RTXF- 11708LL



GEAR Eaton-Fuller 11708 8
Kapacitet: 13 liter

ANVEND	KLIMA
Terrænanvendelse, startservice	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90

Skift alle 2 måneder/ 40 timer

ANVEND	KLIMA
Terrænanvendelse, startservice	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 30	Gear Oil Alcat 30	

Skift alle 2 måneder/ 40 timer

ANVEND	KLIMA
Motorvejsanvendelse, startservice	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90

Skift alle 8000 km

ANVEND	KLIMA
Motorvejsanvendelse, startservice	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 30	Gear Oil Alcat 30	

Skift alle 8000 km

ANVEND	KLIMA
Standard, linjetransport	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90

Skift alle 100000 km

ANVEND	KLIMA
Standard, linjetransport	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 30	Gear Oil Alcat 30	

Skift alle 100000 km

ANVEND	KLIMA
Standard, varevogn/bus	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90

Skift alle 100000 km/ 12 måneder

EATON FULLER TRANSMISSIONER 8 HASTIGHEDER, TUNG BELASTNING RTXF- 11708LL



ANVEND		KLIMA
Standard, varevogn/bus		Arktisk
PRODUKTANBEFALING 1 Multifleet SCD 30	PRODUKTANBEFALING 2 Gear Oil Alcat 30	
Skift alle 100000 km/ 12 måneder		
ANVEND		KLIMA
Standard, stationær		Moderat
PRODUKTANBEFALING 1 Multifleet SCD 50	PRODUKTANBEFALING 2 Multifleet SCD 40	PRODUKTANBEFALING 3 Gearlube GL-4 80W-90
Skift alle 500 timer/ 12 måneder		
ANVEND		KLIMA
Standard, stationær		Arktisk
PRODUKTANBEFALING 1 Multifleet SCD 30	PRODUKTANBEFALING 2 Gear Oil Alcat 30	
Skift alle 500 timer/ 12 måneder		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.