

EATON FULLER TRANSMISSIONER 9 HASTIGHEDER, TUNG BELASTNING RT- 11109A-ATR



GEAR Eaton-Fuller 11109 9/1
Kapacitet: 42 liter

ANVEND

Terrænanvendelse, startservice

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

PRODUKTANBEFALING 2

Gear Oil Alcat 10W

PRODUKTANBEFALING 3

ATF Dexron II-D

Skift alle 30 timer

ANVEND

Motorvejsanvendelse, startservice

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

PRODUKTANBEFALING 2

Gear Oil Alcat 10W

PRODUKTANBEFALING 3

ATF Dexron II-D

Skift alle 2500 km

ANVEND

Terrænanvendelse, svær

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

PRODUKTANBEFALING 2

Gear Oil Alcat 10W

PRODUKTANBEFALING 3

ATF Dexron II-D

Kontroller alle 40 timer, skift alle 500 timer

ANVEND

Terrænanvendelse

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

PRODUKTANBEFALING 2

Gear Oil Alcat 10W

PRODUKTANBEFALING 3

ATF Dexron II-D

Kontroller alle 40 timer, skift alle 1000 timer

ANVEND

Motorvejsanvendelse

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

PRODUKTANBEFALING 2

Gear Oil Alcat 10W

PRODUKTANBEFALING 3

ATF Dexron II-D

Kontroller alle 4000 km, skift alle 80000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.