

# EATON FULLER TRANSMISSIONER 9

## HASTIGHEDER, TUNG BELASTNING RTOF-11909MLL



**GEAR** Eaton-Fuller 11909 9  
Kapacitet: 13 liter

|                                |         |
|--------------------------------|---------|
| ANVEND                         | KLIMA   |
| Terrænanvendelse, startservice | Moderat |

|                          |                          |                             |
|--------------------------|--------------------------|-----------------------------|
| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
| <b>Multifleet SCD 50</b> | <b>Multifleet SCD 40</b> | <b>Gearlube GL-4 80W-90</b> |

Skift alle 2 måneder/ 40 timer

|                                |         |
|--------------------------------|---------|
| ANVEND                         | KLIMA   |
| Terrænanvendelse, startservice | Arktisk |

|                          |                          |  |
|--------------------------|--------------------------|--|
| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2      |  |
| <b>Multifleet SCD 30</b> | <b>Gear Oil Alcat 30</b> |  |

Skift alle 2 måneder/ 40 timer

|                                   |         |
|-----------------------------------|---------|
| ANVEND                            | KLIMA   |
| Motorvejsanvendelse, startservice | Moderat |

|                          |                          |                             |
|--------------------------|--------------------------|-----------------------------|
| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
| <b>Multifleet SCD 50</b> | <b>Multifleet SCD 40</b> | <b>Gearlube GL-4 80W-90</b> |

Skift alle 8000 km

|                                   |         |
|-----------------------------------|---------|
| ANVEND                            | KLIMA   |
| Motorvejsanvendelse, startservice | Arktisk |

|                          |                          |  |
|--------------------------|--------------------------|--|
| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2      |  |
| <b>Multifleet SCD 30</b> | <b>Gear Oil Alcat 30</b> |  |

Skift alle 8000 km

|                          |         |
|--------------------------|---------|
| ANVEND                   | KLIMA   |
| Standard, linjetransport | Moderat |

|                          |                          |                             |
|--------------------------|--------------------------|-----------------------------|
| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
| <b>Multifleet SCD 50</b> | <b>Multifleet SCD 40</b> | <b>Gearlube GL-4 80W-90</b> |

Skift alle 100000 km

|                          |         |
|--------------------------|---------|
| ANVEND                   | KLIMA   |
| Standard, linjetransport | Arktisk |

|                          |                          |  |
|--------------------------|--------------------------|--|
| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2      |  |
| <b>Multifleet SCD 30</b> | <b>Gear Oil Alcat 30</b> |  |

Skift alle 100000 km

|                        |         |
|------------------------|---------|
| ANVEND                 | KLIMA   |
| Standard, varevogn/bus | Moderat |

|                          |                          |                             |
|--------------------------|--------------------------|-----------------------------|
| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
| <b>Multifleet SCD 50</b> | <b>Multifleet SCD 40</b> | <b>Gearlube GL-4 80W-90</b> |

Skift alle 100000 km/ 12 måneder

# EATON FULLER TRANSMISSIONER 9

## HASTIGHEDER, TUNG BELASTNING RTOF-11909MLL



| ANVEND                           |                          | KLIMA                       |
|----------------------------------|--------------------------|-----------------------------|
| Standard, varevogn/bus           |                          | Arktisk                     |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2      |                             |
| <b>Multifleet SCD 30</b>         | <b>Gear Oil Alcat 30</b> |                             |
| Skift alle 100000 km/ 12 måneder |                          |                             |
| ANVEND                           |                          | KLIMA                       |
| Standard, stationær              |                          | Moderat                     |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
| <b>Multifleet SCD 50</b>         | <b>Multifleet SCD 40</b> | <b>Gearlube GL-4 80W-90</b> |
| Skift alle 500 timer/ 12 måneder |                          |                             |
| ANVEND                           |                          | KLIMA                       |
| Standard, stationær              |                          | Arktisk                     |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2      |                             |
| <b>Multifleet SCD 30</b>         | <b>Gear Oil Alcat 30</b> |                             |
| Skift alle 500 timer/ 12 måneder |                          |                             |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.